



flow Star GTS 125 wall conduct

Product number: 4033042

Configuration: white, stainless steel

Configuration options

4033042 | white, stainless steel

- ✓ Wall sleeve
- ✓ installation in the wall

With connection to round pipe Ø 125 mm and round external stainless-steel cover.

- required opening pressure 100 Pa
- stainless steel cover Ø 197 mm
- hose/pipe connector Ø 125 mm
- connector depth 24 mm
- installation depth 314–550 mm, can be shortened to 250 mm, wall penetration Ø about 132 mm
- for the installation of the mounting pipe, a core drilling hole (Ø 132 mm) is recommended



[more infos...](#)

Technical data

| | | | |
|-----------------|----------------------------|-----------------------|--|
| Article type | Wall sleeve | Support depth | 24 mm |
| Material | stainless steel | Installation depth | 314–550 mm |
| Properties | can be shortened | Wall box version | with connection to round pipe Ø 125 mm and round external stainless-steel cover. |
| Mounting/Fixing | installation in the wall | Pipe socket dimension | hose/pipe connector Ø 125 mm |
| Certification | stainless | System dimension | 125 |
| Shortenability | can be shortened to 250 mm | Output drive | round |
| Shape | round | Ventilation system | COMPAIR flow 125 |
| Outer diameter | 125 mm | Opening pressure | 100 Pa |