



Guidance colour change LED

Product number: 7065040

Configuration: L 900 mm, 12.4 W, stainless steel coloured

Configuration options

7065040 | L 900 mm, 12.4 W, stainless steel coloured 7065041 | L 1200 mm, 18.6 W, stainless steel coloured 7065042 | L 1500 mm, 21.7 W, stainless steel coloured

- ✓ Pendant light
- ✓ 2700 K warm white to 6500 K cold white
- √ 12.4 watts

Pendant light. Aluminium body. Incl. converter and 1-channel colour change remote control.

- 230 V
- stepless control of the light colour from 2700 K warm white to 6500 K cold white
- memory function: the last setting is saved
- dimmer function: brightness continuously dimmable
- not dimmable with on-site dimmer
- max. 83 lumen/watt at 6500 K cold white
- suspension max. 1850 mm
- can be operated with the 1- or 4-channel radio remote control
- LIC LED system compatible

This product contains a light source of energy efficiency class G.





more infos...

Technical data

Article type	Luminaire	Colour temperature	2700 K warm white to 6500 K cold white
Width	900 mm	Colour temperature adjustable	stepless
Energy efficiency class	G	Type of dimming	brightness continuously dimmable
Mains voltage	230 V	LIC system compatible	Yes
Transformer / converter required	Yes, included	Illuminant type	LED
Mounting/Fixing	Ceiling mounting	Replaceable illuminant	No
Material housing	aluminium	Light yield	83 lumen/watt
Switch	No	Connection	One-sided
Shape	straight	Suspension	1850 mm
Memory function	Yes	Dimmable by on-site dimmer	No
Illuminant included	Yes	Design	Pendant light
Dimmer	Yes	Dimming function (composite)	Yes, brightness continuously dimmable
Housing colour	stainless-steel coloured	Illuminant power	12.4 watts

Accessories

7061285	1-channel colour change remote control, white
7061276	4 channel colour change remote control, white



Dimensional sketch (PDF)

