




Feel LED

Product number: 7062287

Configuration: subsequent lamp without switch, L 600 mm, 5 W

Configuration options

7062280 | single lamp with switch, L 450 mm, 3.6 W
 7062281 | single lamp with switch, L 600 mm, 5 W
 7062282 | single lamp with switch, L 800 mm, 7 W
 7062283 | single lamp with switch, L 900 mm, 7.9 W
 7062284 | single lamp with switch, L 1000 mm, 8.9 W
 7062285 | single lamp with switch, L 1200 mm, 11 W
 7062286 | subsequent lamp without switch, L 450 mm, 3.6 W
 7062287 | subsequent lamp without switch, L 600 mm, 5 W
 7062288 | subsequent lamp without switch, L 800 mm, 7 W
 7062289 | subsequent lamp without switch, L 900 mm, 7.9 W
 7062290 | subsequent lamp without switch, L 1000 mm, 8.9 W
 7062291 | subsequent lamp without switch, L 1200 mm, 11 W

- ✓ linear light
- ✓ Under-cabinet/niche light
- ✓ 4300 K neutral white

Lamp mounted from below. Aluminium profile, **aluminium coloured**, 120 LEDs/m, no visible LED points.

The lights can easily be extended by simply plugging together the connecting cables integrated in the body caps.

Single lamp with switch

- touch switch and dimmer on the left or right
- **4300 K** neutral white
- memory function: the last setting is stored
- dimmer function: brightness continuously dimmable
- 85 lumen/watt
- 2000 mm supply line rear left or right
- ready for connection to LED converter (7062211 or 7062218)

This product contains a light source of energy efficiency class G.



[more infos...](#)

Technical data

Article type	Luminaire	Illuminant included	Yes
Height	17 mm	Dimmer	Yes
Width	600 mm	Colour temperature	4300 K neutral white
Energy efficiency class	G	Type of dimming	brightness continuously dimmable
Transformer / converter required	Yes, must be ordered separately	Illuminant type	LED
Protection class	III	Replaceable illuminant	No
Mounting/Fixing	pluggable	Light yield	85 lumen/watt
Material housing	aluminium	Connection	One-sided
Certification	CE	Homogeneous light field without visible LED points	Yes
Switch	No	Touch function	Yes
Shape	angular	Design	linear light Under-cabinet/niche light
Memory function	Yes	Dimming function (composite)	Yes, brightness continuously dimmable
Length of the supply line (primary)	2.000 mm	Illuminant power	5 watts