





Kickspace KS 600

Product number: 6011002 Configuration: W 376 mm

Configuration options

6011002 | W 376 mm

\checkmark Base heating system

The compact base-installed heating system for rooms up to about 16 $\rm m^2$ can be connected to the central heating system with much effort.

- connected load 230 V/50 Hz
- heating system exclusively for 2-pipe system
- minimum base height 125 mm

Cover plates need to be ordered separately.

PLEASE OBSERVE:

For proper operation, the average feed temperature should not fall below 60 °C.

The heat output of the device depends on the feed temperature and the flow rate of the heating system.

more infos...

Technical data

| Article type | Base heating system |
|----------------|--|
| Width | 376 mm |
| Standards | the noise levels were tested according to EN 23741. |
| Mains voltage | 230 V |
| Plug type | Angle plug |
| Note | Cover plates need to be ordered separately. For proper operation, the average feed temperature should not fall below 60 °C. The heat output of the device depends on the feed temperature and the flow rate of the heating system. |
| Switch | Yes |
| Heating medium | water |

| For room size | 16 m² |
|--------------------------------------|--------------|
| Minimum plinth height | 125 mm |
| Heating capacity | 981 - 1256 W |
| Suitable pipe system | 2-pipe |
| Engine power | 40 W |
| Mains frequency | 50 Hz |
| Connection to central heating system | Yes |

Accessories

| 6011011 | Room thermostat 230 V, Accessory, white |
|---------|--|
| 6011010 | Reinforced hose, Hose, L 700 mm |
| 6011015 | Reinforced hose, Hose, L 1000 mm |
| 6011016 | Reinforced hose, Hose, L 1500 mm |
| 6011018 | Kickspace-cover, Accessory, KS 600, W 550 mm, stainless-steel coloured |