





Riflettore colour change LED

Product number: 7061333

Configuration: individual lamp without switch, stainless steel

coloured

Configuration options

7061332 | individual lamp without switch, black matt

7061333 | individual lamp without switch, stainless steel coloured

- ✓ Built-in lamp
- \checkmark 2700 K warm white to 6500 K cold white
- √ 2.9 watts

Built-in lamp. Metal body.

Individual lamp without switch

- 2.9 watts, 12 V
- continuous control of the light colour from 2700 K warm white to 6500 K cold white
- dimmer function: brightness continuously dimmable
- max. 87 lumen/watt at 6500 K cold white
- 2000 mm supply line with mini-plug-in system
- drill Ø 55-58 mm
- installation depth 12 mm
- LIC LED system compatible

This product contains a light source of energy efficiency class F.

More information about the LIC LED system







more infos...

Technical data

Article type	Luminaire
Drilling diameter	55-58 mm
Width	70 mm
Energy efficiency class	F
Transformer / converter required	Yes, must be ordered separately
Mounting/Fixing	Base unit installation (wall unit/shelf) installation
Material housing	metal
Switch	No
Shape	round
Length of the supply line (primary)	2.000 mm
Outer diameter	70 mm
Installation depth	12 mm
Illuminant included	Yes
Dimmer	Yes

Housing colour	stainless-steel coloured
Colour temperature	2700 K warm white to 6500 K cold white
Colour temperature adjustable	stepless
Type of dimming	brightness continuously dimmable
LIC system compatible	Yes
Plug-in system	with mini plug-in system
Illuminant type	LED
Replaceable illuminant	No
Light yield	max. 87 lumen/watt at 6500 K cold white
Connection	One-sided
Design	Built-in lamp
Dimming function (composite)	Yes, brightness continuously dimmable
Illuminant power	2.9 watts



Accessories

7061131	Colour change LED Touch switch and dimmer, Switch, stainless steel coloured
7061271	FW function converter, module 2 (radio), 30 W, 6-way distributor
7061281	FW function converter, module 3 (Bluetooth + radio), 30 W, 6-way distributor
7061049	LED connection line, Connecting element, white, L 2000 mm
7061025	LED converter 12, grey
7061403	MEC Driver LED converter, 60/72 W, 12/24 V
7061426	MEC Driver LED 1-channel module radio/ZigBee, Accessory, 12 V
7061428	MEC Driver LED 4-channel module radio/ZigBee, Accessory, 12 V
7061431	MEC Driver LED remote control 1+4 channel ZigBee, white