



Riflettore colour change LED

Product number: 7061333

Configuration: individual lamp without switch, stainless steel coloured

Configuration options

7061332 | individual lamp without switch, black matt

7061333 | individual lamp without switch, stainless steel coloured

- ✓ Built-in lamp
- ✓ 2700 K warm white to 6500 K cold white
- ✓ 2.9 watts

Built-in lamp. Metal body.

Individual lamp without switch

- 2.9 watts, 12 V
- continuous control of the light colour from 2700 K warm white to 6500 K cold white
- dimmer function: brightness continuously dimmable
- max. 87 lumen/watt at 6500 K cold white
- 2000 mm supply line with mini-plug-in system
- drill Ø 55–58 mm
- installation depth 12 mm
- LIC/MEC LED system compatible

This product contains a light source of energy efficiency class F.

More information about the LIC/MEC LED system



[more infos...](#)

Technical data

Article type	Luminaire	Housing colour	stainless-steel coloured
Drilling diameter	55-58 mm	Colour temperature	2700 K warm white to 6500 K cold white
Width	70 mm	Colour temperature adjustable	stepless
Energy efficiency class	F	Type of dimming	brightness continuously dimmable
Transformer / converter required	Yes, must be ordered separately	LIC system compatible	Yes
Mounting/Fixing	Base unit installation (wall unit/shelf) installation	Plug-in system	with mini plug-in system
Material housing	metal	Illuminant type	LED
Switch	No	Replaceable illuminant	No
Shape	round	Light yield	max. 87 lumen/watt at 6500 K cold white
Length of the supply line (primary)	2.000 mm	Connection	One-sided
Outer diameter	70 mm	Design	Built-in lamp
Installation depth	12 mm	Dimming function (composite)	Yes, brightness continuously dimmable
Illuminant included	Yes	Illuminant power	2.9 watts
Dimmer	Yes		

Accessories

7061131	Colour change LED Touch switch and dimmer, Switch, stainless steel coloured
7061271	FW function converter, module 2 (radio), 30 W, 6-way distributor
7061281	FW function converter, module 3 (Bluetooth + radio), 30 W, 6-way distributor
7061049	LED connection line, Connecting element, white, L 2000 mm
7061025	LED converter 12, grey
7061403	MEC Driver LED converter, 60/72 W, 12/24 V
7061426	MEC Driver LED 1-channel module radio/ZigBee, Accessory, 12 V
7061428	MEC Driver LED 4-channel module radio/ZigBee, Accessory, 12 V
7061431	MEC Driver LED remote control 1+4 channel ZigBee, white