



1362

Cingue LED

Product number: 7065026

Configuration: L 1362 mm, 60 W, stainless steel coloured

Configuration options

7065026 | L 1362 mm, 60 W, stainless steel coloured

- ✓ Pendant light
- √ 2700 K warm white to 6500 K cold white
- 60 watts

Pendant light. 6 lights. Aluminium body. Cover in toughened safety glass, opal white. Incl. converter and remote control.

- 230 \
- stepless control of the light colour from 2700 K warm white to 6500 K cold white
- memory function: the last setting is saved
- dimmer function: brightness continuously dimmable
- not dimmable with on-site dimmer
- max. 106 lumen/watt at 6500 K cold white
- lighting elements cannot be moved
- suspension max. 1700 mm

This product contains a light source of energy efficiency class F.







more infos...

Technical data

Article type	Luminaire
Width	1.362 mm
Energy efficiency class	F
Mains voltage	230 V
Transformer / converter required	Yes, included
Mounting/Fixing	Ceiling mounting
Material housing	aluminium
Certification	CE MM sign
Switch	No
Shape	angular
Memory function	Yes
Illuminant included	Yes
Dimmer	Yes
Housing colour	stainless-steel coloured
Colour temperature	2700 K warm white to 6500 K cold white

Colour temperature adjustable	stepless
Type of dimming	brightness continuously dimmable
Illuminant type	LED
Replaceable illuminant	No
Light yield	max. 106 lumen/watt at 6500 K cold white
Connection	One-sided
Material cover	safety glass (ESG)
Cover colour	opal white
Suspension	1700 mm
Number of lamps	6
Dimmable by on-site dimmer	No
Design	Pendant light
Dimming function (composite)	Yes, brightness continuously dimmable
Illuminant power	60 watts



Dimensional sketch (PDF)

