




Ø 105 Ø 115



Twist USB A

Product number: 7053172

Configuration: with earthed plug socket, white matt

Configuration options

7053170 | with earthed plug socket, stainless steel col.

7053171 | with earthed plug socket, black matt

7053172 | with earthed plug socket, white matt

7053173 | with Belgian/French socket, stainless steel coloured

7053174 | with Belgian/French socket, black matt

7053175 | with Belgian/French socket, white matt

- √ Built-in socket element
- √ 1 x earthed plug socket
- √ round

Socket element. 1-fold and double USB charger (charging station).

- 3680 watt/16 A, 250 VAC, IP20
- 2 x USB charger type A, 5 VDC, IA/I out: 2 x 1550 mA
- H05VV-F 3G1
- 3-pole with earthing contact
- 2000 mm mains connection line, with earthed plug enclosed loose
- drill Ø 105 mm, for plate thickness from 8 mm
- increased contact protection
- cable outlet rear side



more infos...



Technical data

Article type	Socket element
Drilling diameter	105 mm
Mains voltage	250 VAC
Protection class	IP20
Cable outlet	cable outlet rear side
Max. connected load	3680 watt
Mounting/Fixing	installation in the worktop
Further	3-pole with earthing contact
Certification	CE
Shape	round
Length of the supply line (primary)	2.000 mm
Installation depth	40 mm
Version sockets	1 x earthed plug socket
Mains plug loosely enclosed	Yes
Colour bezel	white matt

Colour socket	black
Installation diameter	115 mm
Cover/blind type	Turning lid
Integrated water drain	Yes
Number of USB ports	1
USB type	USB-A
Type of socket element	Built-in socket element
Rated current	16 A
Wiring	3-wire with free ends bared
Number of sockets (total)	1
Opening mechanism	Push-to-open
Touch protection ("child safety lock")	with increased contact protection
Worktop thickness	8 mm
USB version	$2 \times \text{USB}$ charger type A, 5 VDC, IA/ I out: $2 \times 1550 \text{ mA}$

Accessories

7053024 Hole saw, Ø 105 mm, for Twist a	nd Duplex
---	-----------