



Twist 2 double plug socket

Product number: 7053194

Configuration: round, Ø 115, D ca. 45 mm, black matt

Configuration options

- 7053190 | round, Ø 115, D ca. 45 mm, stainless steel coloured
- 7053191 | square, L 115, B 115, D ca. 45 mm, stainless steel coloured
- 7053194 | round, Ø 115, D ca. 45 mm, black matt
- 7053195 | square, L 115, B 115, D ca. 45 mm, black matt

- ✓ Built-in socket element
- ✓ 2 x earthed plug socket
- ✓ round

Socket element. 2-fold.

- 3680 watt/16 A, 250 VAC, IP20
- H05VV-F 3G1
- 3-pin with earthing contact
- with earthed plug sockets
- 2000 mm mains connection line, earthing contact plug enclosed loosely
- drill Ø 105 mm, for board thicknesses from 6–40 mm
- increased contact protection
- anti-fingerprint coating
- cable outlet below side
- removable lid for cleaning or subsequent replacement
- automatically cushioned opening mechanism



[more infos...](#)

Technical data

Article type	Socket element	Version sockets	2 x earthed plug socket
Drilling diameter	105 mm	Mains plug loosely enclosed	Yes
Width	115 mm	Colour bezel	black matt
Mains voltage	250 VAC	Colour socket	black
Protection class	IP20	Cover/blind type	Turning lid
Cable outlet	cable outlet rear side	Integrated water drain	Yes
Max. connected load	3680 watt	Type of socket element	Built-in socket element
Mounting/Fixing	in the worktop	Rated current	16 A
Note	can be retrofitted	Wiring	3-wire with free ends
Further	3-pole with earthing contact	Number of sockets (total)	2
Surface/coating	anti-fingerprint coating	Opening mechanism	Push-to-open
Shape	round	Touch protection ("child safety lock")	with increased contact protection
Length of the supply line (primary)	2.000 mm	Worktop thickness	6–40 mm
Installation depth	40 mm		

Accessories

7053024	Hole saw, Ø 105 mm, for Twist and Duplex
---------	--

Dimensional sketch (PDF)

