



## SERVIZIO Namor® 4 window fitting

Product number: 5025036

Configuration: black matt, high pressure

### Configuration options

5025035 | stainless steel, high pressure

5025036 | black matt, high pressure

✓ Sink faucet

✓ high pressure

✓ Swivelling

Single lever faucet. With swivelling/pull-out hose with shower head (can be switched to stream or shower), side lever, laminar aerator and ceramic cartridge.

— height when tilted only 50 mm

— swivel range 120°

— drill Ø 35 mm

— corresponds to the German and European drinking water regulation/directive



[more infos...](#)

### Technical data

|                                      |                                                                                                           |                          |                                                                  |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------|
| Article type                         | Sink faucet                                                                                               | Factory customer service | Factory customer service in Germany, Austria and the Netherlands |
| Brand                                | SERVIZIO                                                                                                  | Type of fitting          | Single lever faucet                                              |
| Number of handles                    | 1                                                                                                         | Operating pressure       | high pressure                                                    |
| Outreach                             | 219 mm                                                                                                    | Width                    | 48 mm                                                            |
| Outlet                               | Swivelling Extractable                                                                                    | Material                 | stainless steel                                                  |
| Discharge height                     | 270 mm                                                                                                    | Surface/coating          | powder coated                                                    |
| Operating mode                       | Lever                                                                                                     | Window fitting           | Yes                                                              |
| Drilling diameter                    | 35 mm                                                                                                     | Swivel range handle      | 0 °                                                              |
| Handle position                      | right                                                                                                     | Number of tap holes      | 1                                                                |
| Lever length                         | 106 mm                                                                                                    | ECO function             | energy-saving cold start function                                |
| Manufacturer's warranty              | 5 years manufacturer's warranty (except on wearing parts)<br>15-year after-sales guarantee on spare parts | Convertible jet/shower   | Yes                                                              |
| Cartridge with ceramic sealing discs | Yes                                                                                                       | Length shower hose       | 820 mm                                                           |
| Swivel range outlet                  | 120°                                                                                                      | Height tilted            | 50 mm                                                            |
| Beam type                            | Laminar beam                                                                                              | Connection hoses         | 820 mm                                                           |