




## Technical data

Article type	Sink faucet	Operating pressure	high pressure
Brand	KWC	Width	50 mm
Number of handles	1	Material	brass
Total installation height	419 mm	Further	LEDs integrated in the shower head illuminate the water jet and create a captivating light sculpture At the push of a button, LED-Shine stages a dance of light with the faucet's water jet. After 45 minutes, the light switches off automatically. Easy Lock – simple return of the pull-out shower head hose surface matches the faucet surface
Outreach	225 mm	Hose thread	3/8"
Outlet	Swivelling Extractable	Worktop thickness	45 mm
Discharge height	259 mm	Swivel range handle	110 °
Operating mode	Lever	TouchProtect	Yes
Drilling diameter	35 mm	Number of tap holes	1
Handle position	left or right	Temperature limiter/scald protection	Yes
Lever length	62 mm	Convertible jet/shower	Yes
Manufacturer's warranty	5 years manufacturer's warranty 10-year after-sales guarantee on spare parts	Spring-guided hose shower	No
Cartridge with ceramic sealing discs	Yes	Angle of inclination of aerator	15 °
Swivel range outlet	320°	Temperature adjustable	Yes
Factory customer service	Yes	With mains plug	Yes
Type of fitting	Single lever faucet	Type of hose shower	Integrated hose spray

## Dimensional sketch (PDF)

## KWC EVE



KWC-Nr.	Oberfläche
<b>10.121.103.000FL</b>	ganzchrom
A 225, flexible Anschlussschläuche, Netz AP	
<b>10.121.103.700FL</b>	edelstahl
A 225, flexible Anschlussschläuche, Netz AP	

## KWC



### Küche mit LEDShine

LUMINAQUA®  
Advanced Light Technology

EDELSTAHL  
STAINLESS STEEL



#### Hebelmischer

- Positionierung des Hebels rechts oder links möglich
- TouchProtect - Schutz vor Verbrennungen durch Zweischalenprinzip
- Auszugauslauf verdeckt
  - Neoperl® Caché®
  - integrierter ON/OFF Taster mit Abschaltautomatik nach 45 Minuten
  - bis 600 mm ausziehbar
  - Schlauchoberfläche passend zu Armaturoberfläche
- Schlauchdurchführung, schwenkbar 320°
- EasyLock - einfache Auszugbrausenrückführung
- OptimalSpace - grosszügiger Wasch- / Arbeitsbereich
- KWC Steuerpatrone M 35
  - mit Keramikscheibentechnik
  - Auslaufmenge und Temperatur stufenlos einstellbar
- Flexible Anschlussschläuche 3/8"
- Befestigung mit Gewindestützen M33 x 1.5
- Tischbohrung ø35 mm
- Lieferumfang:
  - Steckernetzteil 100-240 V / Betriebsspannung 6.75 V / Kabellänge 1100 mm

Auslaufmenge 10 l/min (3 bar)  
Armaturengeräuschgruppe I

Sortiments, Modell- und technische Änderungen vorbehalten. Massangaben in mm.

www.kwc.com 08.01.2021