



Ricol colour change LED

Product number: 7061184

Configuration: single lamp without switch, L 2600 mm, stainless

steel coloured

Configuration options

7060105 | single lamp without switch, L 2600 mm, black matt 7060106 | single lamp without switch, L 1500 mm, black matt 7061184 | single lamp without switch, L 2600 mm, stainless steel coloured 7061195 | single lamp without switch, L 1500 mm, stainless steel coloured

- √ Built-in lamp
- ✓ linear light
- √ 2700 K warm white to 6500 K cold white

Built-in lamp. Aluminium body, LED built-in profile, hidden cable routing with clamp fastening, no screws required.

Individual lamp without switch

- 15.5 watts per meter
- continuous control of the light colour from 2700 K warm white to 6500 K cold white
- max. 80 lumen/watt at 6000 K cold white
- light length 2600 mm
- LED strip loose, not used in profile
- can be shortened every 25 mm, two-sided feed-in
- 2000 mm two-sided supply line
- 4 end caps enclosed separately
- connection to 12 V converter with colour change control
- installation depth 12 mm
- LIC LED system compatible

This product contains a light source of energy efficiency class F.

More information about the LIC LED system





more infos...



Technical data

Article type	Luminaire	
Width	2.600 mm	
Energy efficiency class	F	
Transformer / converter required	Yes, must be ordered separately	
Protection class	III	
Mounting/Fixing	With concealed fastening clampable	
Material housing	aluminium	
Switch	No	
Shortenability	may be shortened every 25 mm	
Shape	angular	
Length of the supply line (primary)	2.000 mm	
More parts	incl. 4 end caps	
Installation depth	12 mm	

Illuminant included	Yes
Housing colour	stainless-steel coloured
Colour temperature	2700 K warm white to 6500 K cold white
Colour temperature adjustable	stepless
LIC system compatible	Yes
Illuminant type	LED
Replaceable illuminant	Yes
Light yield	max. 80 lumen/watt at 6000 K cold white
Light yield With spring clips for installation in cavity ceilings	
With spring clips for installation in	cold white
With spring clips for installation in cavity ceilings	cold white Yes
With spring clips for installation in cavity ceilings Connection Homogeneous light field without visible	cold white Yes On both sides

Accessories

7061049	LED connection line, Connecting element, white, L 2000 mm
7061304	Light profile colour change LED strip, LED stripe, L 2600 mm, 40.3 W/12 V
7061144	Colour change LED extension set, , white
7061286	FW function converter, module 2 (radio), 15 W, 4-way distributor
7061271	FW function converter, module 2 (radio), 30 W, 6-way distributor
7061273	FW function converter, module 2 (radio), 60 W, 6-way distributor
7061281	FW function converter, module 3 (Bluetooth + radio), 30 W, 6-way distributor
7061287	FW function converter, module 3 (Bluetooth + radio), 15 W, 4-way distributor
7061283	FW function converter, module 3 (Bluetooth + radio), 60 W, 6-way distributor
7061285	1-channel colour change remote control, white
7061403	MEC Driver LED converter, 60/72 W, 12/24 V
7061426	MEC Driver LED 1-channel module radio/ZigBee, Accessory, 12 V
7061428	MEC Driver LED 4-channel module radio/ZigBee, Accessory, 12 V
7061431	MEC Driver LED remote control 1+4 channel ZigBee, white