



## Ricol colour change LED

Product number: 7061184

Configuration: single lamp without switch, L 2600 mm, stainless steel coloured

### Configuration options

7060105 | single lamp without switch, L 2600 mm, black matt

7060106 | single lamp without switch, L 1500 mm, black matt

7061184 | single lamp without switch, L 2600 mm, stainless steel coloured

7061195 | single lamp without switch, L 1500 mm, stainless steel coloured

- ✓ Built-in lamp
- ✓ linear light
- ✓ 2700 K warm white to 6500 K cold white

Built-in lamp. Aluminium body, LED built-in profile, hidden cable routing with clamp fastening, no screws required.

Individual lamp without switch

- 15.5 watts per meter
- continuous control of the light colour from 2700 K warm white to 6500 K cold white
- max. 80 lumen/watt at 6000 K cold white
- light length 2600 mm
- LED strip loose, not used in profile
- can be shortened every 25 mm, two-sided feed-in
- 2000 mm two-sided supply line
- 4 end caps enclosed separately
- connection to 12 V converter with colour change control
- installation depth 12 mm
- LIC/MEC LED system compatible

This product contains a light source of energy efficiency class F.

More information about the LIC/MEC LED system



[more infos...](#)

## Technical data

Article type	Luminaire	Illuminant included	Yes
Width	2.600 mm	Housing colour	stainless-steel coloured
Energy efficiency class	F	Colour temperature	2700 K warm white to 6500 K cold white
Transformer / converter required	Yes, must be ordered separately	Colour temperature adjustable	stepless
Protection class	III	LIC system compatible	Yes
Mounting/Fixing	With concealed fastening clampable	Illuminant type	LED
Material housing	aluminium	Replaceable illuminant	Yes
Switch	No	Light yield	max. 80 lumen/watt at 6000 K cold white
Shortenability	may be shortened every 25 mm	With spring clips for installation in cavity ceilings	Yes
Shape	angular	Connection	On both sides
Length of the supply line (primary)	2.000 mm	Homogeneous light field without visible LED points	Yes
More parts	incl. 4 end caps	Design	Built-in lamp linear light
Installation depth	12 mm	Power per metre	15.5 watts

## Accessories

7061049	LED connection line, Connecting element, white, L 2000 mm
7061304	Light profile colour change LED strip, LED stripe, L 2600 mm, 40.3 W/12 V
7061144	Colour change LED extension set, Luminaire, white
7061286	FW function converter, module 2 (radio), 15 W, 4-way distributor
7061271	FW function converter, module 2 (radio), 30 W, 6-way distributor
7061273	FW function converter, module 2 (radio), 60 W, 6-way distributor
7061281	FW function converter, module 3 (Bluetooth + radio), 30 W, 6-way distributor
7061287	FW function converter, module 3 (Bluetooth + radio), 15 W, 4-way distributor
7061283	FW function converter, module 3 (Bluetooth + radio), 60 W, 6-way distributor
7061285	1-channel colour change remote control, white
7061403	MEC Driver LED converter, 60/72 W, 12/24 V
7061426	MEC Driver LED 1-channel module radio/ZigBee, Accessory, 12 V
7061428	MEC Driver LED 4-channel module radio/ZigBee, Accessory, 12 V
7061431	MEC Driver LED remote control 1+4 channel ZigBee, white