



## Ricol colour change LED

Product number: 7061184

Configuration: single lamp without switch, L 2600 mm, stainless steel coloured

### Configuration options

7060105 | single lamp without switch, L 2600 mm, black matt

7060106 | single lamp without switch, L 1500 mm, black matt

7061184 | single lamp without switch, L 2600 mm, stainless steel coloured

7061195 | single lamp without switch, L 1500 mm, stainless steel coloured

- ✓ Built-in lamp
- ✓ linear light
- ✓ 2700 K warm white to 6500 K cold white

Built-in lamp. Aluminium body, LED built-in profile, hidden cable routing with clamp fastening, no screws required.

### Individual lamp without switch

- 15.5 watts per meter
- continuous control of the light colour from **2700 K** warm white to **6500 K** cold white
- max. 80 lumen/watt at **6000 K** cold white
- light length 2600 mm
- LED strip loose, not used in profile
- can be shortened every 25 mm, two-sided feed-in
- 2000 mm two-sided supply line
- 4 end caps enclosed separately
- connection to 12 V converter with colour change control
- installation depth 12 mm
- LIC/MEC LED system compatible

**This product contains a light source of energy efficiency class F.**

More information about the LIC/MEC LED system



[more infos...](#)

## Technical data

Article type	Luminaire	Illuminant included	Yes
Height	11,4 mm	Housing colour	stainless-steel coloured
Width	2.600 mm	Colour temperature	2700 K warm white to 6500 K cold white
Energy efficiency class	F	Colour temperature adjustable	stepless
Transformer / converter required	Yes, must be ordered separately	LIC system compatible	Yes
Protection class	III	Illuminant type	LED
Mounting/Fixing	With concealed fastening clampable	Replaceable illuminant	Yes
Material housing	aluminium	Light yield	max. 80 lumen/watt at 6000 K cold white
Switch	No	With spring clips for installation in cavity ceilings	Yes
Shortenability	may be shortened every 25 mm	Connection	On both sides
Shape	angular	Homogeneous light field without visible LED points	Yes
Length of the supply line (primary)	2.000 mm	Design	Built-in lamp linear light
More parts	incl. 4 end caps	Power per metre	15.5 watts
Installation depth	12 mm		