



## Twist 2 double plug socket

Product number: 7053190

Configuration: round, Ø 115, D ca. 45 mm, stainless steel coloured

### Configuration options

7053190 | round, Ø 115, D ca. 45 mm, stainless steel coloured

7053191 | square, L 115, B 115, D ca. 45 mm, stainless steel coloured

7053194 | round, Ø 115, D ca. 45 mm, black matt

7053195 | square, L 115, B 115, D ca. 45 mm, black matt

- ✓ Built-in socket element
- ✓ 2 x earthed plug socket
- ✓ round

Socket element. 2-fold.

- 3680 watt/16 A, 250 VAC, IP20
- H05VV-F 3G1
- 3-pin with earthing contact
- with earthed plug sockets
- 2000 mm mains connection line, earthing contact plug enclosed loosely
- drill Ø 105 mm, for board thicknesses from 6–40 mm
- increased contact protection
- anti-fingerprint coating
- cable outlet below side
- removable lid for cleaning or subsequent replacement
- automatically cushioned opening mechanism



[more infos...](#)

### Technical data

Article type	Socket element	Version sockets	2 x earthed plug socket
Drilling diameter	105 mm	Mains plug loosely enclosed	Yes
Width	115 mm	Colour bezel	stainless-steel coloured
Mains voltage	250 VAC	Colour socket	black
Protection class	IP20	Cover/blind type	Turning lid
Cable outlet	cable outlet rear side	Integrated water drain	Yes
Max. connected load	3680 watt	Type of socket element	Built-in socket element
Mounting/Fixing	in the worktop	Rated current	16 A
Note	can be retrofitted	Wiring	3-wire with free ends
Further	3-pole with earthing contact	Number of sockets (total)	2
Surface/coating	anti-fingerprint coating	Opening mechanism	Push-to-open
Shape	round	Touch protection ("child safety lock")	with increased contact protection
Length of the supply line (primary)	2.000 mm	Worktop thickness	6–40 mm
Installation depth	40 mm		

### Accessories

7053024	Hole saw, Ø 105 mm, for Twist and Duplex
---------	--

Dimensional sketch (PDF)

