



## Twist 2 double plug socket

Product number: 7053190

Configuration: round, Ø 115, D ca. 45 mm, stainless steel coloured

### Configuration options

7053190 | round, Ø 115, D ca. 45 mm, stainless steel coloured

7053191 | square, L 115, B 115, D ca. 45 mm, stainless steel coloured

7053194 | round, Ø 115, D ca. 45 mm, black matt

7053195 | square, L 115, B 115, D ca. 45 mm, black matt

- ✓ Built-in socket element
- ✓ 2 x earthen plug socket
- ✓ round

Socket element. 2-fold.

- 3680 watt/16 A, 250 VAC, IP20
- H05VV-F 3G1
- 3-pin with earthing contact
- with earthen plug sockets
- 2000 mm mains connection line, earthing contact plug enclosed loosely
- drill Ø 105 mm, for board thicknesses from 6–40 mm
- increased contact protection
- anti-fingerprint coating
- cable outlet below side
- **removable lid for cleaning or subsequent replacement**
- **automatically cushioned opening mechanism**



[more infos...](#)

### Technical data

|                                     |                              |                                        |                                   |
|-------------------------------------|------------------------------|----------------------------------------|-----------------------------------|
| Article type                        | Socket element               | Installation depth                     | 40 mm                             |
| Height                              | 115 mm                       | Version sockets                        | 2 x earthen plug socket           |
| Drilling diameter                   | 105 mm                       | Mains plug loosely enclosed            | Yes                               |
| Width                               | 115 mm                       | Colour bezel                           | stainless-steel coloured          |
| Mains voltage                       | 250 VAC                      | Colour socket                          | black                             |
| Protection class                    | IP20                         | Cover/blind type                       | Turning lid                       |
| Cable outlet                        | cable outlet rear side       | Integrated water drain                 | Yes                               |
| Max. connected load                 | 3680 watt                    | Type of socket element                 | Built-in socket element           |
| Mounting/Fixing                     | in the worktop               | Rated current                          | 16 A                              |
| Note                                | can be retrofitted           | Wiring                                 | 3-wire with free ends             |
| Further                             | 3-pole with earthing contact | Number of sockets (total)              | 2                                 |
| Surface/coating                     | anti-fingerprint coating     | Opening mechanism                      | Push-to-open                      |
| Shape                               | round                        | Touch protection ("child safety lock") | with increased contact protection |
| Length of the supply line (primary) | 2.000 mm                     | Worktop thickness                      | 6–40 mm                           |

Dimensional sketch (PDF)

