



Twist 2 double plug socket

Product number: 7053190
Configuration: round, Ø 115, D ca. 45 mm, stainless steel coloured

Configuration options
7053190 | round, Ø 115, D ca. 45 mm, stainless steel coloured
7053191 | square, L 115, B 115, D ca. 45 mm, stainless steel coloured
7053194 | round, Ø 115, D ca. 45 mm, black matt
7053195 | square, L 115, B 115, D ca. 45 mm, black matt

✓ Built-in socket element
✓ 2 x earthed plug socket
✓ round

Socket element. 2-fold.
— 3680 watt/16 A, 250 VAC, IP20
— H05VV-F 3G1
— 3-pin with earthing contact
— with earthed plug sockets
— 2000 mm mains connection line with earthing contact plug enclosed loosely
— drill Ø 105 mm, for board thicknesses from 6–40 mm
— increased contact protection
— anti-fingerprint coating
— cable outlet below side
— **removable lid for cleaning or subsequent replacement**
— **automatically cushioned opening mechanism**

CE

more infos...

Technical data

Article type	Socket element	Installation depth	40 mm
Height	115 mm	Version sockets	2 x earthed plug socket
Drilling diameter	105 mm	Mains plug loosely enclosed	Yes
Width	115 mm	Colour bezel	stainless-steel coloured
Mains voltage	250 VAC	Colour socket	black
Protection class	IP20	Cover/blind type	Turning lid
Cable outlet	cable outlet rear side	Integrated water drain	Yes
Max. connected load	3680 watt	Type of socket element	Built-in socket element
Mounting/Fixing	in the worktop	Rated current	16 A
Note	can be retrofitted	Wiring	3-wire with free ends
Further	3-pole with earthing contact	Number of sockets (total)	2
Surface/coating	anti-fingerprint coating	Opening mechanism	Push-to-open
Shape	round	Touch protection ("child safety lock")	with increased contact protection
Length of the supply line (primary)	2.000 mm	Worktop thickness	6–40 mm

Dimensional sketch (PDF)



