



Profile light Neva LED

Product number: 7062510
Configuration: L 600 mm, 9.6 W

Configuration options
7062510 | L 600 mm, 9.6 W
7062511 | L 900 mm, 14.4 W
7062512 | L 1200 mm, 19.2 W
7062513 | L 1500 mm, 24 W

✓ linear light
✓ Under-cabinet/niche light
✓ 3000 K warm white, 4000 K neutral white, 5000 K cold white

Lamp for mounting from below. Plastic housing with overlapping end caps. Can be shortened every 50 mm. Illumination without visible LED points with integrated switch.

Individual lamp with switch

— 16 watts per meter, 24 V, three colour ranges: **3000 K** warm white, **4000 K** neutral white, **5000 K** cold white
— 75 lumen/watt
— very high quality of light thanks to colour rendering index >90
— sliding switch on each light for adjustable light colour: warm white/neutral white/ cool white
— memory function: the last setting is stored
— dimming function: brightness can be continuously dimmed
— 2000 mm supply line with mini-plug-in system
— incl. fastening clips
— incl. 30 watt converter

This product contains a light source with the energy efficiency class E.

CE

more infos...

Naber GmbH
Enschedestr. 24
DE-48529 Nordhorn

Tel. +49 5921 704-0
Fax +49 5921 704-140
naber@naber.com

Technical data

Article type	Luminaire
Height	12,4 mm
Width	600 mm
Material	aluminium
Energy efficiency class	E
Mains voltage	12 VDC
Transformer / converter required	Yes, included
Protection class	IP20
Protection class	III
Mounting/Fixing	Base unit installation (wall unit/ shelf)
Further	sliding switch on each light for adjustable light colour: warm white/ neutral white/ cool white
Certification	CE
Switch	Yes
Shortenability	may be shortened every 50 mm
Shape	angular
Memory function	Yes

Length of the supply line (primary)	2.000 mm
More parts	incl. mounting clips
Dimmer	Yes
Colour temperature	3000 K warm white, 4000 K neutral white, 5000 K cold white
Type of dimming	brightness continuously dimmable
Illuminant type	LED
Colour rendering index	>90
Light yield	75 lumen/watt
Material cover	plastic
Homogeneous light field without visible LED points	Yes
Radiation angle	113°
Design	linear light Under-cabinet/niche light
Dimming function (composite)	Yes, brightness continuously dimmable
Power per metre	16 watts
Illuminant power	9.6 watts

Naber GmbH
Enschedestr. 24
DE-48529 Nordhorn

Tel. +49 5921 704-0
Fax +49 5921 704-140
naber@naber.com

Dimensional sketch (PDF)

