



## Duplex E double socket

Product number: 7054003

Configuration: square, with earthed plug sockets, stainless steel

### Configuration options

- 7054001 | round, with earthed plug sockets, stainless steel
- 7054003 | square, with earthed plug sockets, stainless steel
- 7054005 | square, with earthed plug sockets, black matt
- 7054008 | round, with earthed plug sockets, black matt

- ✓ Built-in socket element
- ✓ 2 x earthed plug socket
- ✓ square

Socket element. Double. Electric opening at the push of a button.

- 3680 watt/16 A, 250 VAC, IP20
- H05VV-F 3G 1.5 mm<sup>2</sup>
- 3-pole with earthing contact
- 2000 mm mains connection line with earthing contact plug
- drill Ø 105 mm
- installation depth approx. 48 mm
- increased contact protection
- space-saving cable routing (downwards or side cable outlet)
- simple and quick installation
- retrofitting possible
- integrated water drain



[more infos...](#)

### Technical data

|                                     |                                    |  |                                   |
|-------------------------------------|------------------------------------|--|-----------------------------------|
| Article type                        | Socket element                     | Version sockets                        | 2 x earthed plug socket           |
| Height                              | 118 mm                             | Mains plug loosely enclosed            | Yes                               |
| Drilling diameter                   | 105 mm                             | Colour bezel                           | Stainless steel                   |
| Width                               | 118 mm                             | Colour socket                          | black                             |
| Mains voltage                       | 250 VAC                            | Cover/blind type                       | Electric                          |
| Protection class                    | IP20                               | Integrated water drain                 | Yes                               |
| Cable outlet                        | cable outlet on the side or bottom | Type of socket element                 | Built-in socket element           |
| Max. connected load                 | 3680 watt                          | Switch type                            | Touch switch                      |
| Mounting/Fixing                     | in the worktop installation        | Conductor cross-section                | 1,5 mm <sup>2</sup>               |
| Note                                | can be retrofitted                 | Rated current                          | 16 A                              |
| Further                             | 3-pole with earthing contact       | Wiring                                 | bared<br>3-wire with free ends    |
| Certification                       | CE<br>TÜV                          | Number of sockets (total)              | 2                                 |
| Shape                               | square                             | Opening mechanism                      | Push & Pull                       |
| Length of the supply line (primary) | 2.000 mm                           | Touch protection ("child safety lock") | with increased contact protection |
| Installation depth                  | 48 mm                              |  |                                   |