





Kludi M2

Product number: 5023076

Configuration: chrome, high pressure

Configuration options

5023076 | chrome, high pressure

- \checkmark Sink faucet
- √ high pressure
- √ Swivelling

Single lever faucet. With swivelling outlet and ceramic cartridge with hot-water limiter.

- swivel range 360°
- drill Ø 35 mm
- including DO-IT connection hoses





more infos...



Technical data

BrandKludiFactory customer serviceYesNumber of handles1Type of fittingSingle lever faucetTotal installation height235 mmOperating pressurehigh pressureOutreach220 mmWidth52 mmOutletSwivellingMounting/Fixingincluding DO-IT connection hosesDischarge height170 mmWorktop thickness1-40 mmOperating modeLeverNumber of tap holes1Drilling diameter35 mmTemperature limiter/scald protectionYesHandle positiontopAnti-limestone jet regulatorYes	Article type	Sink faucet	Swivel range outlet	360°
Total installation height 235 mm Operating pressure high pressure Outreach 220 mm Width 52 mm Outlet Swivelling Mounting/Fixing including DO-IT connection hoses Discharge height 170 mm Worktop thickness 1–40 mm Operating mode Lever Number of tap holes 1 Drilling diameter 35 mm Temperature limiter/scald protection Yes	Brand	Kludi	Factory customer service	Yes
Outreach220 mmWidth52 mmOutletSwivellingMounting/Fixingincluding DO-IT connection hosesDischarge height170 mmWorktop thickness1–40 mmOperating modeLeverNumber of tap holes1Drilling diameter35 mmTemperature limiter/scald protectionYes	Number of handles	1	Type of fitting	Single lever faucet
Outlet Swivelling Mounting/Fixing including DO-IT connection hoses Discharge height 170 mm Worktop thickness 1–40 mm Operating mode Lever Number of tap holes 1 Drilling diameter 35 mm Temperature limiter/scald protection Yes	Total installation height	235 mm	Operating pressure	high pressure
Discharge height 170 mm Worktop thickness 1–40 mm Operating mode Lever Number of tap holes 1 Drilling diameter 35 mm Temperature limiter/scald protection Yes	Outreach	220 mm	Width	52 mm
Operating mode Lever Number of tap holes 1 Drilling diameter 35 mm Temperature limiter/scald protection Yes	Outlet	Swivelling	Mounting/Fixing	including DO-IT connection hoses
Drilling diameter 35 mm Temperature limiter/scald protection Yes	Discharge height	170 mm	Worktop thickness	1–40 mm
	Operating mode	Lever	Number of tap holes	1
Handle position top Anti-limestone jet regulator Yes	Drilling diameter	35 mm	Temperature limiter/scald protection	Yes
	Handle position	top	Anti-limestone jet regulator	Yes
	Lever length	95 mm	Angle of inclination of aerator	15,3 °
Manufacturer's warranty 5 years manufacturer's warranty Flow rate at 3 bar (cold) 9 l/min (except on wearing parts) 10-year after-sales guarantee on spare parts	Manufacturer's warranty	(except on wearing parts) 10-year after-sales guarantee on	Flow rate at 3 bar (cold)	9 l/min
Cartridge with ceramic sealing discs Yes	Cartridge with ceramic sealing discs	Yes		