

Edition colour change LED 1

Product number: 7062531

Configuration: black matt

Configuration options

7062530 | roestvrij staalkleurig

7062531 | black matt

✓ Under-cabinet/niche light

✓ 2200 K warm white to 6500 K cold white

✓ 4.3 watts

Lamp mounted from below. Anodised aluminium housing with plastic covers. Innovative lighting technology with a PMMA lens. Easy snap-in installation: single light fitting without a switch

— 4.3 watts, 24 V

— stepless control of the light colour from **2200 K** warm white to **6500 K** cold white

— max. 100 lumen/watt

— very high quality of light thanks to colour rendering index > 90


— dimming function: brightness can be continuously dimmed

— 2000 mm supply line

— replaceable LED strip module

— LIC 2.0/MEC LED system compatible

This product contains a light source with the energy efficiency class E.



[more infos...](#)

Technical data

Article type	Luminaire	Dimmer	Yes
Height	15,3 mm	Housing colour	black matt
Width	19 mm	Colour temperature	2200 K warm white to 6500 K cold white
Energy efficiency class	E	Colour temperature adjustable	stepless
Transformer / converter required	Yes, must be ordered separately	Type of dimming	brightness continuously dimmable
Mounting/Fixing	Base unit installation (wall unit/shelf)	Plug-in system	with mini plug-in system
Material housing	aluminium	Illuminant type	LED
Certification	CE	Colour rendering index	>90
Switch	No	Replaceable illuminant	Yes
Shape	angular	Design	Under-cabinet/niche light
Memory function	Yes	Dimming function (composite)	Yes, brightness continuously dimmable
Length of the supply line (primary)	2.000 mm	Illuminant power	4.3 watts
Illuminant included	Yes		