




# Edition colour change LED 1

Product number: 7062531
Configuration: black matt

**Configuration options**
7062530 | roestvrij staalkleurig
7062531 | black matt

✓ Under-cabinet/niche light
✓ 2200 K warm white to 6500 K cold white
✓ 4.3 watts

Lamp mounted from below. Anodised aluminium housing with plastic covers. Innovative lighting technology with a PMMA lens. Easy snap-in installation: single light fitting without a switch
— 4.3 watts, 24 V
— stepless control of the light colour from **2200 K** warm white to **6500 K** cold white
— max. 100 lumen/watt
— very high quality of light thanks to colour rendering index >90
— dimming function: brightness can be continuously dimmed
— 2000 mm supply line
— replaceable LED strip module
— LIC 2.0/MEC LED system compatible
**This product contains a light source with the energy efficiency class E.**

CE

more infos...

## Technical data

| | | | |
|---|---|---|---|
| Article type | Luminaire | Dimmer | Yes |
| Height | 15,3 mm | Housing colour | black matt |
| Width | 19 mm | Colour temperature | 2200 K warm white to 6500 K cold white |
| Energy efficiency class | E | Colour temperature adjustable | stepless |
| Transformer / converter required | Yes, must be ordered separately | Type of dimming | brightness continuously dimmable |
| Mounting/Fixing | Base unit installation (wall unit/shelf) | Plug-in system | with mini plug-in system |
| Material housing | aluminium | Illuminant type | LED |
| Certification | CE | Colour rendering index | >90 |
| Switch | No | Replaceable illuminant | Yes |
| Shape | angular | Design | Under-cabinet/niche light |
| Memory function | Yes | Dimming function (composite) | Yes, brightness continuously dimmable |
| Length of the supply line (primary) | 2.000 mm | Illuminant power | 4.3 watts |
| Illuminant included | Yes | | |