



Edition colour change LED 1

Product number: 7062531
Configuration: black matt

Configuration options
7062530 | roestvrij staalkleurig
7062531 | black matt

✓ Under-cabinet/niche light
✓ 2200 K warm white to 6500 K cold white
✓ 4.3 watts

Lamp mounted from below. Anodised aluminium housing with plastic covers. Innovative lighting technology with a PMMA lens. Easy snap-in installation: single light fitting without a switch
— 4.3 watts, 24 V
— stepless control of the light colour from **2200 K** warm white to **6500 K** cold white
— max. 100 lumen/watt
— very high quality of light thanks to colour rendering index >90
— dimming function: brightness can be continuously dimmed
— 2000 mm supply line
— replaceable LED strip module
— LIC 2.0/MEC LED system compatible
This product contains a light source with the energy efficiency class E.

CE

more infos...

Technical data

Article type	Luminaire	Dimmer	Yes
Height	15,3 mm	Housing colour	black matt
Width	19 mm	Colour temperature	2200 K warm white to 6500 K cold white
Energy efficiency class	E	Colour temperature adjustable	stepless
Transformer / converter required	Yes, must be ordered separately	Type of dimming	brightness continuously dimmable
Mounting/Fixing	Base unit installation (wall unit/shelf)	Plug-in system	with mini plug-in system
Material housing	aluminium	Illuminant type	LED
Certification	CE	Colour rendering index	>90
Switch	No	Replaceable illuminant	Yes
Shape	angular	Design	Under-cabinet/niche light
Memory function	Yes	Dimming function (composite)	Yes, brightness continuously dimmable
Length of the supply line (primary)	2.000 mm	Illuminant power	4.3 watts
Illuminant included	Yes		