

## Lupo LED

Product number: 7062255

Configuration: L 900 mm, 15 W, aluminium coloured

### Configuration options

7062253 | L 450 mm, 8 W, aluminium coloured  
 7062254 | L 600 mm, 10 W, aluminium coloured  
 7062255 | L 900 mm, 15 W, aluminium coloured  
 7062256 | L 1200 mm, 18 W, aluminium coloured  
 7062293 | L 450 mm, 8 W, black matt  
 7062294 | L 600 mm, 10 W, black matt  
 7062295 | L 900 mm, 15 W, black matt  
 7062296 | L 1200 mm, 18 W, black matt



- ✓ linear light
- ✓ Under-cabinet/niche light
- ✓ 3900 K neutral white

Lamp mounted from below. Aluminium body with plastic cover, head to head installation possible.

### Individual lamp with switch

- 230 V (**high voltage**), 3900 K neutral white
- 75 lumen/watt
- 14 x 40 mm (H x W)
- 80 mm connection line
- cable outlet rear left side of lamp
- when connecting several lights (e.g. with end-to-end mounting or using a connecting cable), the existing “back-to-back” connectors allow each light to be switched on and off independently of the others
- **max. 200 watts can be connected**
- mains connection HV (7062249 white or 7062269 black) to be ordered separately

This product contains a light source of energy efficiency class G.



[more infos...](#)

### Technical data

|                                  |                                                |                                     |                                           |
|----------------------------------|------------------------------------------------|-------------------------------------|-------------------------------------------|
| Article type                     | Luminaire                                      | Shape                               | angular                                   |
| Height                           | 14 mm                                          | Length of the supply line (primary) | 80 mm                                     |
| Width                            | 900 mm                                         | Illuminant included                 | Yes                                       |
| Energy efficiency class          | G                                              | Colour temperature                  | 3900 K neutral white                      |
| Mains voltage                    | 230 V                                          | Illuminant type                     | LED                                       |
| Transformer / converter required | No. Mains cable HV must be ordered separately. | Replaceable illuminant              | No                                        |
| Mounting/Fixing                  | Base unit installation (wall unit/shelf)       | Light yield                         | 75 lumen/watt                             |
| Note                             | max. 10 lamps can be connected                 | Connection                          | One-sided                                 |
| Material housing                 | aluminium                                      | Material cover                      | plastic                                   |
| Certification                    | CE                                             | Design                              | linear light<br>Under-cabinet/niche light |
| Switch                           | Yes                                            | Illuminant power                    | 15 watts                                  |