



## Easytrack Sun Romo

Product number: 7065132

Configuration: black matt

### Configuration options

7065132 | black matt

- ✓ Pendant light
- ✓ 2700 K warm white to 6000 K cold white
- ✓ 37 watts

Pendant light for Easytrack busbar. Aluminium housing powder-coated.

— 37 watt, 48 VDC

— stepless control of the light colour from **2700 K** warm white to **6000 K** cold white

— very high light quality thanks to colour rendering index > 90

— max. 52 lumen/watt at **6000 K** cold white

— the maximum pendant length is 1500 mm and can be continuously adjusted.

— with integrated Zigbee 3.0 controller

**This product contains a light source with the energy efficiency class F.**

**Tool-free click-in installation in the track. Is held in place by mechanical locking!**



[more infos...](#)

### Technical data

|                         |                                                                                       |                                |                                         |
|-------------------------|---------------------------------------------------------------------------------------|--------------------------------|-----------------------------------------|
| Article type            | Luminaire                                                                             | Colour temperature adjustable  | stepless                                |
| Height                  | 40 mm                                                                                 | Type of dimming                | brightness continuously dimmable        |
| Width                   | 1.450 mm                                                                              | Illuminant type                | LED                                     |
| Material                | aluminium                                                                             | Colour rendering index         | >90                                     |
| Energy efficiency class | F                                                                                     | Light yield                    | max. 52 lumen/watt at 6000 K cold white |
| Mains voltage           | 48 VDC                                                                                | Suspension                     | max. 1500 mm                            |
| Smarthome               | ZigBee 3.0                                                                            | Number of lamps                | 1                                       |
| Mounting/Fixing         | tool-free click-in installation in the track<br>held in place by a mechanical locking | Segments infinitely adjustable | Yes                                     |
| Material housing        | aluminium                                                                             | Radiation angle                | 70°                                     |
| Certification           | CE                                                                                    | Dimmable by on-site dimmer     | No                                      |
| Surface/coating         | powder coated                                                                         | Design                         | Pendant light                           |
| Shape                   | straight                                                                              | Dimming function (composite)   | brightness continuously dimmable        |
| Illuminant included     | Yes                                                                                   | Illuminant power               | 37 watts                                |
| Colour temperature      | 2700 K warm white to 6000 K cold white                                                |                                |                                         |