

Easytrack pendant S

Product number: 7065074

Configuration: black matt


Configuration options

7065074 | black matt

- ✓ Pendant light
- ✓ 2700 K warm white to 6000 K cold white
- ✓ 5 watts

Pendant light. Pendant S for Easytrack track. Powder-coated aluminium housing.

- 5 Watt, 48 VDC
- L 300 mm, Ø 30 mm
- Infinitely variable adjustment of light colour from 2700 K warm white to 6000 K cool white
- Very high quality of light thanks to colour rendering index > 90
- max. 70 lumens/watt at 6000 K cool white
- pendant length incl. luminaire continuously adjustable from 400 mm to 1600 mm
- with integrated ZigBee 3.0 control unit This product contains a light source of energy efficiency class F. Tool-free click-in installation in the track. Held in place by magnet or additional mechanical lock!



[more infos...](#)

Technical data

Article type	Luminaire	Type of dimming	brightness continuously dimmable
Width	300 mm	LIC system compatible	Yes
Material	aluminium	Illuminant type	LED
Energy efficiency class	F	Colour rendering index	>90
Mains voltage	48 VDC	Light yield	max. 70 lumen/watt at 6000 K cold white
Smarthome	ZigBee 3.0	Suspension	incl. light continuously adjustable from 400 mm to 1600 mm
Mounting/Fixing	tool-free click-in installation in the track Held in place by a magnet or by additional mechanical locking!	Number of lamps	1
Certification	CE	Segments infinitely adjustable	Yes
Surface/coating	powder coated	Design	Pendant light
Illuminant included	Yes	Dimming function (composite)	brightness continuously dimmable
Colour temperature	2700 K warm white to 6000 K cold white	Illuminant power	5 watts
Colour temperature adjustable	stepless		