# Vidula colour change LED

Product number: 7061294
Configuration: L 1500 mm, stainless steel coloured

**Configuration options**
7061223 | L 2600 mm, stainless steel coloured
7061224 | L 2600 mm, black matt
7061294 | L 1500 mm, stainless steel coloured
7061295 | L 1500 mm, black matt
7061308 | L 600 mm, stainless steel coloured
7061309 | L 600 mm, black matt
7061310 | L 900 mm, stainless steel coloured
7061311 | L 900 mm, black matt
7061312 | L 1200 mm, stainless steel coloured
7061313 | L 1200 mm, black matt

✓ Under-cabinet/niche light

✓ linear light

✓ 2700 K warm white to 6500 K cold white
Lamp mounted from below. Aluminium housing, with matt plastic cover including LED profile.

Individual lamp without switch
— 12 watts per meter
— continuous control of the light colour from 2700 K warm white to 6500 K cold white
— max. 92 lumen/watt at 6000 K cold white
— LED strip loose, not used in profile from a length of 1500 mm
— can be shortened every 25 mm
— 2000 mm two-sided supply line from a length of 1500 mm
— 2 end caps enclosed loose, from a length of 1500 mm 4 end caps
— connection to 12 V converter with colour change control
— LIC LED system compatible
This product contains a light source of energy efficiency class G.

More information about the LIC LED system

more infos...

## Technical data

| | | | |
|---|---|---|---|
| Article type | Luminaire | Illuminant included | Yes |
| Width | 1.500 mm | Housing colour | stainless-steel coloured |
| Energy efficiency class | G | Colour temperature | 2700 K warm white to 6500 K cold white |
| Transformer / converter required | Yes, must be ordered separately | Colour temperature adjustable | stepless |
| Mounting/Fixing | Base unit installation (wall unit/shelf) | LIC system compatible | Yes |
| Material housing | aluminium | Illuminant type | LED |
| Certification | CE<br>MM sign | Replaceable illuminant | Yes |
| | | Light yield | max. 92 lumen/watt at 6000 K cold white |
| Switch | No | Connection | On both sides |
| Shortenability | may be shortened every 25 mm | Material cover | plastic |
| Shape | angular | Design | Under-cabinet/niche light<br>linear light |
| Length of the supply line (primary) | 2.000 mm | | |
| More parts | incl. 4 end caps | Power per metre | 12 watts |

## Accessories

| | |
|---|---|
| 7061049 | LED connection line, Connecting element, white, L 2000 mm |
| 7061306 | Vidula colour change LED strip, LED stripe, L 2600 mm |
| 7061286 | FW function converter, module 2 (radio), 15 W, 4-way distributor |
| 7061271 | FW function converter, module 2 (radio), 30 W, 6-way distributor |
| 7061273 | FW function converter, module 2 (radio), 60 W, 6-way distributor |
| 7061287 | FW function converter, module 3 (Bluetooth + radio), 15 W, 4-way distributor |
| 7061281 | FW function converter, module 3 (Bluetooth + radio), 30 W, 6-way distributor |
| 7061283 | FW function converter, module 3 (Bluetooth + radio), 60 W, 6-way distributor |
| 7061285 | 1-channel colour change remote control, white |
| 7061403 | MEC Driver LED converter, 60/72 W, 12/24 V |
| 7061426 | MEC Driver LED 1-channel module radio/ZigBee, Accessory, 12 V |
| 7061428 | MEC Driver LED 4-channel module radio/ZigBee, Accessory, 12 V |
| 7061431 | MEC Driver LED remote control 1+4 channel ZigBee, white |