



Hull colour change LED

Product number: 7061140

Configuration: single lamp without switch, LIC/MEC LED system compatible, stainless steel coloured

Configuration options

7061140 | single lamp without switch, LIC/MEC LED system compatible, stainless steel coloured

7061141 | set 2, stainless steel coloured

7061142 | set 3, stainless steel coloured

7061143 | set 5, stainless steel coloured

✓ Under-cabinet/niche light

✓ 2700 K warm white to 6500 K cold white

✓ 5.5 watts

Lamp mounted from below. Plastic body, translucent light diffuser, homogenous illumination without visible LED points.

Individual lamp without switch

— 5.5 watts, 12 V

— continuous control of the light colour from 2700 K warm white to 6500 K cold white

— memory function: the last setting is stored

— dimmer function: brightness continuously dimmable

— max. 74.5 lumen/watt at 6500 K cold white

— 1800 mm supply line with mini-plug-in system

Set 2, 3, 5 with colour change LED Touch switch and dimmer consisting of:

— 2, 3 or 5 individual lamps without switch (7061140)

— 1 colour change LED Touch switch and dimmer (7061131)

— 1 LED converter 30 (7061026)

This product contains a light source of energy efficiency class D.

More information about the LIC/MEC LED system



[more infos...](#)

Technical data

| | | | |
|-------------------------------------|--|--|---|
| Article type | Luminaire | Colour temperature | 2700 K warm white to 6500 K cold white |
| Width | 187 mm | Colour temperature adjustable | stepless |
| Energy efficiency class | D | Type of dimming | brightness continuously dimmable |
| Transformer / converter required | Yes, must be ordered separately | LIC system compatible | Yes |
| Protection class | IP20 | Plug-in system | with mini plug-in system |
| Protection class | III | Illuminant type | LED |
| Mounting/Fixing | Base unit installation (wall unit/shelf) | Replaceable illuminant | No |
| Material housing | plastic | Light yield | max. 74,5 lumen/watt at 6500 K cold white |
| Certification | CE MM sign | Cover colour | transparent |
| Switch | No | Number of light points | 60 |
| Shape | angular | Number of lamps | 60 |
| Memory function | Yes | Homogeneous light field without visible LED points | Yes |
| Length of the supply line (primary) | 1.800 mm | Design | Under-cabinet/niche light |
| Illuminant included | Yes | Dimming function (composite) | Yes, brightness continuously dimmable |
| Dimmer | Yes | Illuminant power | 5.5 watts |
| Housing colour | stainless-steel coloured | | |

Accessories

| | |
|---------|---|
| 7061049 | LED connection line, Connecting element, white, L 2000 mm |
| 7061026 | LED converter 30, grey |
| 7061131 | Colour change LED Touch switch and dimmer, Switch, stainless steel coloured |
| 7061403 | MEC Driver LED converter, 60/72 W, 12/24 V |
| 7061426 | MEC Driver LED 1-channel module radio/ZigBee, Accessory, 12 V |
| 7061428 | MEC Driver LED 4-channel module radio/ZigBee, Accessory, 12 V |
| 7061431 | MEC Driver LED remote control 1+4 channel ZigBee, white |