




Hull colour change LED

Product number: 7061140

Configuration: single lamp without switch, LIC/MEC LED system compatible, stainless steel coloured

Configuration options

7061140 | single lamp without switch, LIC/MEC LED system compatible, stainless steel coloured

- ✓ Under-cabinet/niche light
- ✓ 2700 K warm white to 6500 K cold white
- ✓ 5.5 watts

Lamp mounted from below. Plastic body, translucent light diffuser, homogenous illumination without visible LED points.

Individual lamp without switch

- 5.5 watts, 12 V
- continuous control of the light colour from **2700 K** warm white to **6500 K** cold white
- memory function: the last setting is stored
- dimmer function: brightness continuously dimmable
- max. 74.5 lumen/watt at **6500 K** cold white
- 1800 mm supply line with mini-plug-in system

Set 2, 3, 5 with colour change LED Touch switch and dimmer consisting of:

- 2, 3 or 5 individual lamps without switch (7061140)
- 1 colour change LED Touch switch and dimmer (7061131)
- 1 LED converter 30 (7061026)

This product contains a light source of energy efficiency class D.

More information about the LIC/MEC LED system



[more infos...](#)

Technical data

Article type	Luminaire	Housing colour	stainless-steel coloured
Height	11 mm	Colour temperature	2700 K warm white to 6500 K cold white
Width	187 mm	Colour temperature adjustable	stepless
Energy efficiency class	D	Type of dimming	brightness continuously dimmable
Transformer / converter required	Yes, must be ordered separately	LIC system compatible	Yes
Protection class	IP20	Plug-in system	with mini plug-in system
Protection class	III	Illuminant type	LED
Mounting/Fixing	Base unit installation (wall unit/shelf)	Replaceable illuminant	No
Material housing	plastic	Light yield	max. 74,5 lumen/watt at 6500 K cold white
Certification	CE MM sign	Cover colour	transparent
Switch	No	Number of light points	60
Shape	angular	Number of lamps	60
Memory function	Yes	Homogeneous light field without visible LED points	Yes
Length of the supply line (primary)	1.800 mm	Design	Under-cabinet/niche light
Illuminant included	Yes	Dimming function (composite)	Yes, brightness continuously dimmable
Dimmer	Yes	Illuminant power	5.5 watts