



## Fluente LED aluminium coloured

Product number: 7063435

Configuration: L 900 mm, 15 W, 2900 K warm white

### Configuration options

7063433 | L 450 mm, 8 W, 2900 K warm white  
 7063434 | L 600 mm, 10 W, 2900 K warm white  
 7063435 | L 900 mm, 15 W, 2900 K warm white  
 7063436 | L 1200 mm, 18 W, 2900 K warm white  
 7063437 | L 450 mm, 8 W, 4100 K neutral white  
 7063438 | L 600 mm, 10 W, 4100 K neutral white  
 7063439 | L 900 mm, 15 W, 4100 K neutral white  
 7063440 | L 1200 mm, 18 W, 4100 K neutral white

- ✓ linear light
- ✓ Under-cabinet/niche light
- ✓ 2900 K warm white

Lamp mounted from below. Aluminium body with plastic cover, head to head installation possible.

Individual lamp with switch

- 230 V (high voltage)
  - 75 lumen/watt
  - 14 x 40 mm (H x W)
  - 80 mm connection line
  - cable outlet rear left side of lamp
  - max. 200 watts can be connected
  - mains connection HV (7062249 white or 7062269 black) to be ordered separately
- This product contains a light source of energy efficiency class G.



[more infos...](#)

### Technical data

|                                  |  |                                     |   |
|----------------------------------|--|-------------------------------------|---|
| Article type                     | Luminaire                                      | Length of the supply line (primary) | 80 mm                                     |
| Width                            | 900 mm   | Illuminant included                 | Yes                                       |
| Energy efficiency class          | G  | Colour temperature                  | 2900 K warm white                         |
| Mains voltage                    | 230 V  | Illuminant type                     | LED                                       |
| Transformer / converter required | No. Mains cable HV must be ordered separately. | Replaceable illuminant              | No  |
| Mounting/Fixing                  | Base unit installation (wall unit/shelf)       | Light yield                         | 75 lumen/watt                             |
| Note                             | max. 10 lamps can be connected                 | Connection                          | One-sided                                 |
| Material housing                 | aluminium                                      | Material cover                      | plastic                                   |
| Certification                    | CE   | Design                              | linear light<br>Under-cabinet/niche light |
| Switch                           | Yes  | Illuminant power                    | 15 watts                                  |
| Shape                            | angular  |                                     |   |

**Accessories**

|         |   |
|---------|---|
| 7062249 | Mains connection line HV, Connecting element, white           |
| 7062269 | Mains connection line HV, Connecting element, black           |
| 7062257 | Connecting line HV, Connection line/element, L 150 mm, white  |
| 7062258 | Connecting line HV, Connection line/element, L 500 mm, white  |
| 7062259 | Connecting line HV, Connection line/element, L 1000 mm, white |
| 7062297 | Connecting line HV, Connection line/element, L 150 mm, black  |
| 7062298 | Connecting line HV, Connection line/element, L 500 mm, black  |
| 7062299 | Connecting line HV, Connection line/element, L 1000 mm, black |