





Ideal Standard Ceraflex 5 window fitting

Product number: 5024166

Configuration: chrome, high pressure

Configuration options

5024166 | chrome, high pressure

- \checkmark Sink faucet
- √ high pressure
- √ Swivelling

Single lever faucet. With swivelling outlet and ceramic cartridge.

- height when tilted only 25 mm
- swivel range 360°
- drill Ø 35 mm

German Engineering



more infos...

Technical data

Article type	Sink faucet
Brand	Ideal Standard
Number of handles	1
Total installation height	205 mm
Outreach	228 mm
Outlet	Swivelling
Discharge height	176 mm
Operating mode	Lever
Drilling diameter	35 mm
Handle position	top
Lever length	101 mm
Manufacturer's warranty	5 years manufacturer's warranty 10-year after-sales guarantee on spare parts
Cartridge with ceramic sealing discs	Yes

Swivel range outlet	360°
Factory customer service	Yes
Type of fitting	Single lever faucet
Operating pressure	high pressure
Width	48 mm
Material	brass
Worktop thickness	40 mm
Window fitting	Yes
Number of tap holes	1
Temperature limiter/scald protection	Yes
Height tilted	25 mm
Angle of inclination of aerator	9°
Flow rate at 3 bar (cold)	9 l/min



Accessories

5031005

Dirt Filter Ecco 1, 3/8", chrome