



Klima-E flow 150 wall conduct

Product number: 4044050

Configuration: white

Configuration options

4044050 | white
 4044052 | brick red
 4044062 | light grey
 4044063 | anthracite

✓ Wall sleeve

With backpressure shutter and external blind.

With rectangular connector for COMPAIR® flow 150.

- tube connector 227 x 94 mm
- connector depth 80 mm
- installation depth 420–620 mm, can be shortened to 135 mm
- wall penetration about Ø 155 mm



[more infos...](#)

Technical data

Article type	Wall sleeve	Installation depth	420–620 mm
Properties	can be shortened	Wall box version	rectangular connector for COMPAIR® flow 150 with backpressure shutter and external blind
Shortenability	can be shortened to 135 mm	Pipe socket dimension	pipe connector 227 x 94 mm
Shape	angular	Blind version	with backpressure shutter
Outer diameter	150 mm	System dimension	150
Support depth	80 mm	Output drive	angular
Diameter wall opening	155 mm	Ventilation system	COMPAIR flow 150

Technical drawing of the Naboer K-Klima R flow 150 Mauerkasten. The drawing includes a side view (A-A) showing a cylindrical body with a diameter of 152mm and a total height of 350mm. The top flange has an outer diameter of 180mm and an inner diameter of 89mm. The base has a diameter of 204mm. A cross-section (B-B) shows the internal structure with a total width of 190mm and a central opening of 50mm. A 3D perspective view shows the unit mounted on a wall. The drawing is labeled with dimensions and part numbers.