










# Manubrio colour change LED

Product number: 7061197
Configuration: single lamp, L 2600 mm, stainless steel coloured

**Configuration options**
7060107 | single lamp, L 2600 mm, black matt
7060108 | single lamp, L 1500 mm, black matt
7061197 | single lamp, L 2600 mm, stainless steel coloured
7061298 | single lamp, L 1500 mm, stainless steel coloured

✓ LED Stripe
✓ Base light/niche light
✓ Handle strip lighting

Handle strip lighting. Plastic body, self-adhesive LED strip, can be shortened every 50 mm, no visible LED incl. holding clamps for handle strips.

**Individual lamp**
— 7.8 watts per meter, 12 V
— continuous control of the light colour from **2700 K** warm white to **6500 K** cold white
— max. 80 lumen/watt at **6500 K** cold white
— 2000 mm two-sided supply line
— LED strip, two-sided feed-in
— incl. 4 end caps
— LIC 2.0/MEC LED system compatible
**This product contains a light source of energy efficiency class F.**

More information about the LIC/MEC LED system

CE M M F

more infos...

## Technical data

| | |
|---|---|
| Article type | LED stripe |
| Height | 12 mm |
| Width | 2.600 mm |
| Energy efficiency class | F |
| Transformer / converter required | Yes, must be ordered separately |
| Mounting/Fixing | self-adhesive |
| Material housing | plastic |
| Shortenability | may be shortened every 50 mm |
| Shape | straight |
| Length of the supply line (primary) | 2.000 mm |
| More parts | incl. holding clamps<br>incl. 4 end caps |
| Illuminant included | Yes |

| | |
|---|---|
| Housing colour | stainless-steel coloured |
| Colour temperature | 2700 K warm white to 6500 K cold white |
| Colour temperature adjustable | stepless |
| LIC system compatible | Yes |
| Illuminant type | LED |
| Replaceable illuminant | No |
| Light yield | max. 80 lumen/watt at 6000 K cold white |
| Connection | On both sides |
| Homogeneous light field without visible LED points | Yes |
| Design | LED Stripe<br>Base light/niche light<br>Handle strip lighting |
| Power per metre | 7.8 watts |