




AstraLED SE

Product number: 7063333

Configuration: single lamp without switch, 3000 K warm white

Configuration options

7063333 | single lamp without switch, 3000 K warm white
 7063334 | single lamp w. LED Touch s. d., 3000 K warm white
 7063335 | set-2, 3000 K warm white
 7063336 | set-3, 3000 K warm white
 7063337 | set-5, 3000 K warm white
 7063348 | individual lamp without switch, 3900 K neutral white
 7063349 | single lamp w. LED Touch s. d., 3900 K neutral white
 7063350 | set-2, 3900 K neutral white
 7063351 | set-3, 3900 K neutral white
 7063352 | set-5, 3900 K neutral white

- ✓ Under-cabinet/niche light
- ✓ 3000 K warm white
- ✓ 5 watts

Lamp for mounting from below. Aluminium housing, 5 mm, illumination without visible LED points with integrated touch switch.

Individual lamp without or with LED Touch switch and dimmer (w. LED Touch s. d.)

- 5 watt, 24 V, two colour ranges: **3000 K** warm white, **3900 K** neutral white
- 65 lumen/watt
- brightness continuously dimmable using LED touch switch and dimmer
- 200 mm supply line, 2000 mm connecting line with mini-plug-in system
- additional memory function: the last setting is saved

Set 2, 3, 5 with LED Touch switch and dimmer consisting of:

- 1, 2 or 4 individual lamps with switch (7063333/7063348)
- 1 individual lamp with LED Touch switch and dimmer (7063334/7063349)
- 1 LED converter 2430 (7062250)
- may be extended to 6 lamps

This product contains a light source with the energy efficiency class F.



[more infos...](#)

Technical data

Article type	Luminaire	Illuminant included	Yes
Height	5 mm	Dimmer	Yes
Width	190 mm	Housing colour	black matt
Energy efficiency class	F	Colour temperature	3000 K warm white
Transformer / converter required	Yes, must be ordered separately	Type of dimming	brightness continuously dimmable
Protection class	III	Plug-in system	with mini plug-in system
Mounting/Fixing	Base unit installation (wall unit/ shelf)	Illuminant type	LED
Material housing	aluminium	Replaceable illuminant	No
Length of connection cable (secondary)	2.000 mm	Light yield	65 lumen/watt
Switch	No	Homogeneous light field without visible LED points	Yes
Surface/coating	matt	Touch function	Yes
Shape	angular	Design	Under-cabinet/niche light
Memory function	Yes	Dimming function (composite)	Yes, brightness continuously dimmable
Length of the supply line (primary)	150 mm	Illuminant power	5 watts