



Twist double plug socket

Product number: 7053025

Configuration: with Belgian/French sockets, stainless steel coloured

Configuration options

- 7053021 | with earthed plug sockets, stainless steel coloured
- 7053025 | with Belgian/French sockets, stainless steel coloured
- 7053059 | with Swiss sockets, stainless steel coloured
- 7053075 | with earthed plug sockets, black matt
- 7053076 | with earthed plug sockets, white matt
- 7053085 | with Belgian/French sockets, black matt
- 7053086 | with Belgian/French sockets, white matt
- 7053189 | with Swiss sockets, black matt

- ✓ Built-in socket element
- ✓ 2 x with Belgian/French socket
- ✓ round

Socket element. 2-fold.

- 3680 watt/16 A, 250 VAC, IP20
- H05VV-F 3G1
- 3-pin with earthing contact
- 2000 mm mains connection line, earthing contact plug enclosed loosely
- drill Ø 105 mm, for board thicknesses from 8 mm
- increased contact protection
- cable outlet below side



[more infos...](#)

Technical data

Article type	Socket element	Mains plug loosely enclosed	Yes
Drilling diameter	105 mm	Colour bezel	stainless-steel coloured
Mains voltage	250 VAC	Colour socket	black
Protection class	IP20	Installation diameter	115 mm
Cable outlet	cable outlet rear side	Cover/blind type	Turning lid
Max. connected load	3680 watt	Integrated water drain	Yes
Mounting/Fixing	installation on the worktop	Type of socket element	Built-in socket element
Further	3-pole with earthing contact	Wiring	3-wire with free ends bared
Certification	CE	Number of sockets (total)	2
Shape	round	Opening mechanism	Push-to-open
Length of the supply line (primary)	2.000 mm	Touch protection ("child safety lock")	with increased contact protection
Installation depth	40 mm	Worktop thickness	8 mm
Version sockets	2 x with Belgian/French socket		

Accessories

7053024	Hole saw, Ø 105 mm, for Twist and Duplex
---------	------------------------------------------

Recommendations

7053024	Hole saw, Ø 105 mm, for Twist and Duplex
---------	------------------------------------------