







# Lista 50 colour change LED

Product number: 7062343
Configuration: L 600 mm, 4.3 W, black matt

## Configuration options

7062340 | L 450 mm, 3.1 W, stainless steel coloured
7062341 | L 450 mm, 3.1 W, black matt
7062342 | L 600 mm, 4.3 W, stainless steel coloured
7062343 | L 600 mm, 4.3 W, black matt
7062344 | L 900 mm, 6.6 W, stainless steel coloured
7062345 | L 900 mm, 6.6 W, black matt
7062346 | L 1200 mm, 9 W, stainless steel coloured
7062347 | L 1200 mm, 9 W, black matt

✓ lit glass pane
✓ 2700 K warm white to 6500 K cold white
✓ angular

Lit glass shelf. Aluminium body, mat safety glass, with LED lighting, uniform illumination over the entire width upward and downward, free-hanging attachment up to a shelf depth of 200 mm, screws on the back, mounted invisibly. **Converter not integrated in the lit glass shelf**.

**Lit glass shelf**
— 12 V, IP20
— continuous control of the light colour from **2700 K** warm white to **6500 K** cold white
— max. 64 lumen/watt at **6500 K** cold white
— 2000 mm supply line with mini-plug-in system
— **cable outlet rear left of lamp**
— bearing capacity* approx. 1 kg/100 mm
— incl. angle adjustment
— LIC 2.0/MEC LED system compatible
**This product contains a light source of energy efficiency class G**.

*The load-bearing capacity depends on the wall condition. Suitable mounting material for the respective wall type is to be used.

More information about the LIC/MEC LED system

more infos...

Naber GmbH
Enschedestr. 24
DE-48529 Nordhorn

Tel. +49 5921 704-0
Fax +49 5921 704-140
naber@naber.com

## Technical data

| | |
|---|---|
| Article type | lit glass pane |
| Height | 50 mm |
| Width | 600 mm |
| Energy efficiency class | G |
| Transformer / converter required | Yes, must be ordered separately |
| Protection class | IP20 |
| Protection class | III |
| Mounting/Fixing | Wall mounting<br>screwable<br>Screw fastening |
| Note | * The load-bearing capacity depends on the wall condition. Suitable mounting material for the respective wall type is to be used (not included in scope of delivery). |
| Material housing | aluminium |
| Surface/coating | matt |
| Shape | angular |
| Length of the supply line (primary) | 2.000 mm |
| Carrying capacity | approx. 1.0 kg/100 mm |

| | |
|---|---|
| Illuminant included | Yes |
| Housing colour | black matt |
| Colour temperature | 2700 K warm white to 6500 K cold white |
| Colour temperature adjustable | stepless |
| LIC system compatible | Yes |
| Plug-in system | with mini plug-in system |
| Illuminant type | LED |
| Replaceable illuminant | No |
| Light yield | max. 64 lumen/watt at 6500 K cold white |
| Connection | One-sided |
| Cover colour | transparent |
| Homogeneous light field without visible LED points | Yes |
| Design | lit glass pane |
| Illuminant power | 4.3 watts |

Naber GmbH
Enschedestr. 24
DE-48529 Nordhorn

Tel. +49 5921 704-0
Fax +49 5921 704-140
naber@naber.com