



Profile light Neva LED

Product number: 7062511

Configuration: L 900 mm, 14.4 W

Configuration options

7062510 | L 600 mm, 9.6 W

7062511 | L 900 mm, 14.4 W

7062512 | L 1200 mm, 19.2 W

7062513 | L 1500 mm, 24 W

- ✓ linear light
- ✓ Under-cabinet/niche light
- ✓ 3000 K warm white, 4000 K neutral white, 5000 K cold white

Lamp for mounting from below. Plastic housing with overlapping end caps. Can be shortened every 50 mm. Illumination without visible LED points with integrated switch.

Individual lamp with switch

- 16 watts per meter, 24 V, three colour ranges: **3000 K** warm white, **4000 K** neutral white, **5000 K** cold white
- sliding switch on each light for adjustable light colour: warm white/neutral white/cool white
- 80 lumen/watt
- memory function: the last setting is stored
- dimming function: brightness can be continuously dimmed
- 2000 mm supply line with mini-plug-in system
- incl. fastening clips
- **incl. 30 watt converter**

This product contains a light source with the energy efficiency class E.



[more infos...](#)

Technical data

Article type	Luminaire	Length of the supply line (primary)	2.000 mm
Width	900 mm	More parts	incl. mounting clips
Material	aluminium	Dimmer	Yes
Mains voltage	24 V	Colour temperature	3000 K warm white, 4000 K neutral white, 5000 K cold white
Transformer / converter required	Yes, included	Type of dimming	brightness continuously dimmable
Protection class	IP20	Illuminant type	LED
Protection class	III	Light yield	80 lumen/watt
Mounting/Fixing	Base unit installation (wall unit/shelf)	Material cover	plastic
Further	sliding switch on each light for adjustable light colour: warm white/neutral white/cool white	Homogeneous light field without visible LED points	Yes
Certification	CE	Design	linear light Under-cabinet/niche light
Switch	Yes	Dimming function (composite)	Yes, brightness continuously dimmable
Shortenability	may be shortened every 50 mm	Power per metre	16 watts
Shape	angular	Illuminant power	14.4 watts
Memory function	Yes		