



Feel LED

Product number: 7062290

Configuration: subsequent lamp without switch, L 1000 mm, 8.9 W

Configuration options

7062280 | single lamp with switch, L 450 mm, 3.6 W
 7062281 | single lamp with switch, L 600 mm, 5 W
 7062282 | single lamp with switch, L 800 mm, 7 W
 7062283 | single lamp with switch, L 900 mm, 7.9 W
 7062284 | single lamp with switch, L 1000 mm, 8.9 W
 7062285 | single lamp with switch, L 1200 mm, 11 W
 7062286 | subsequent lamp without switch, L 450 mm, 3.6 W
 7062287 | subsequent lamp without switch, L 600 mm, 5 W
 7062288 | subsequent lamp without switch, L 800 mm, 7 W
 7062289 | subsequent lamp without switch, L 900 mm, 7.9 W
 7062290 | subsequent lamp without switch, L 1000 mm, 8.9 W
 7062291 | subsequent lamp without switch, L 1200 mm, 11 W

- ✓ linear light
- ✓ Under-cabinet/niche light
- ✓ 4300 K neutral white

Lamp mounted from below. Aluminium profile, aluminium coloured, 120 LEDs/m, no visible LED points.

The lights can easily be extended by simply plugging together the connecting cables integrated in the body caps.

Single lamp with switch

- touch switch and dimmer on the left or right
- 4300 K neutral white
- memory function: the last setting is stored
- dimmer function: brightness continuously dimmable
- 85 lumen/watt
- 2000 mm supply line rear left or right
- ready for connection to LED converter (7062211 or 7062218)

This product contains a light source of energy efficiency class G.



[more infos...](#)

Technical data

Article type	Luminaire	Dimmer	Yes
Width	1.000 mm	Colour temperature	4300 K neutral white
Energy efficiency class	G	Type of dimming	brightness continuously dimmable
Transformer / converter required	Yes, must be ordered separately	Illuminant type	LED
Protection class	III	Replaceable illuminant	No
Mounting/Fixing	pluggable	Light yield	85 lumen/watt
Material housing	aluminium	Connection	One-sided
Certification	CE	Homogeneous light field without visible LED points	Yes
Switch	No	Touch function	Yes
Shape	angular	Design	linear light Under-cabinet/niche light
Memory function	Yes	Dimming function (composite)	Yes, brightness continuously dimmable
Length of the supply line (primary)	2.000 mm	Illuminant power	8.9 watts
Illuminant included	Yes		

Accessories

7061049	LED connection line, Connecting element, white, L 2000 mm
7062211	LED converter 6, white
7062218	LED converter 2, blanc