



## Feel LED

Product number: 7062290

Configuration: subsequent lamp without switch, L 1000 mm, 8.9 W

### Configuration options

7062280 | single lamp with switch, L 450 mm, 3.6 W  
 7062281 | single lamp with switch, L 600 mm, 5 W  
 7062282 | single lamp with switch, L 800 mm, 7 W  
 7062283 | single lamp with switch, L 900 mm, 7.9 W  
 7062284 | single lamp with switch, L 1000 mm, 8.9 W  
 7062285 | single lamp with switch, L 1200 mm, 11 W  
 7062286 | subsequent lamp without switch, L 450 mm, 3.6 W  
 7062287 | subsequent lamp without switch, L 600 mm, 5 W  
 7062288 | subsequent lamp without switch, L 800 mm, 7 W  
 7062289 | subsequent lamp without switch, L 900 mm, 7.9 W  
 7062290 | subsequent lamp without switch, L 1000 mm, 8.9 W  
 7062291 | subsequent lamp without switch, L 1200 mm, 11 W

- ✓ linear light
- ✓ Under-cabinet/niche light
- ✓ 4300 K neutral white

Lamp mounted from below. Aluminium profile, **aluminium coloured**, 120 LEDs/m, no visible LED points.

The lights can easily be extended by simply plugging together the connecting cables integrated in the body caps.

### Single lamp with switch

- touch switch and dimmer on the left or right
- **4300 K** neutral white
- memory function: the last setting is stored
- dimmer function: brightness continuously dimmable
- 85 lumen/watt
- 2000 mm supply line rear left or right

**This product contains a light source of energy efficiency class G.**



[more infos...](#)

## Technical data

|                                     |                                 |                                                    |                                           |
|-------------------------------------|---------------------------------|----------------------------------------------------|-------------------------------------------|
| Article type                        | Luminaire                       | Illuminant included                                | Yes                                       |
| Height                              | 17 mm                           | Dimmer                                             | Yes                                       |
| Width                               | 1.000 mm                        | Colour temperature                                 | 4300 K neutral white                      |
| Energy efficiency class             | G                               | Type of dimming                                    | brightness continuously dimmable          |
| Transformer / converter required    | Yes, must be ordered separately | Illuminant type                                    | LED                                       |
| Protection class                    | III                             | Replaceable illuminant                             | No                                        |
| Mounting/Fixing                     | pluggable                       | Light yield                                        | 85 lumen/watt                             |
| Material housing                    | aluminium                       | Connection                                         | One-sided                                 |
| Certification                       | CE                              | Homogeneous light field without visible LED points | Yes                                       |
| Switch                              | No                              | Touch function                                     | Yes                                       |
| Shape                               | angular                         | Design                                             | linear light<br>Under-cabinet/niche light |
| Memory function                     | Yes                             | Dimming function (composite)                       | Yes, brightness continuously dimmable     |
| Length of the supply line (primary) | 2.000 mm                        | Illuminant power                                   | 8.9 watts                                 |