




Giro-S LED

Product number: 7064182

Configuration: L 908 mm, 16 W, silver coloured

Configuration options

7064180 | L 348 mm, 6 W, silver coloured

7064181 | L 576 mm, 10 W, silver coloured

7064182 | L 908 mm, 16 W, silver coloured

7064183 | L 770 mm, 13 W, silver coloured

7064184 | L 1210 mm, 21 W, silver coloured

✓ Under-cabinet/niche light

✓ linear light

✓ 4000 K neutral white

Lamp mounted from below. 150° swivelling LED lamp unit with acrylic cover. Illumination without visible LED points.

The lamps can easily be extended by simply plugging together or using the connection line supplied.

Individual lamp with switch

— 230 V (**high voltage**), 4000 K neutral white

— 75 lumen/watt

— 1800 mm mains connection line enclosed separately

— 300 mm connection line enclosed separately

— additional connector length 60 mm

— cable outlet left side of lamp

— **max. 10 lamps can be connected**

This product contains a light source of energy efficiency class C.



[more infos...](#)

Technical data

Article type	Luminaire	Illuminant included	Yes
Height	27 mm	Colour temperature	4000 K neutral white
Width	908 mm	Swivel range	150 °
Energy efficiency class	C	Illuminant type	LED
Transformer / converter required	No	Replaceable illuminant	No
Mounting/Fixing	pluggable	Light yield	75 lumen/watt
Note	max. 10 lamps can be connected	Connection	One-sided
Length of connection cable (secondary)	300 mm	Material cover	Acrylic glass
Switch	Yes	Homogeneous light field without visible LED points	Yes
Shape	angular	Design	Under-cabinet/niche light linear light
Length of the supply line (primary)	1.800 mm	Illuminant power	16 watts