





## Liente colour change LED wall shelf

Product number: 7062390

Configuration: L 600 mm, 13.8 W, black matt

## **Configuration options**

7062390 | L 600 mm, 13.8 W, black matt 7062391 | L 900 mm, 21 W, black matt 7062392 | L 1200 mm, 28.2 W, black matt

7062393 | L 600 mm, 13.8 W, stainless steel coloured 7062394 | L 900 mm, 21 W, stainless steel coloured 7062395 | L 1200 mm, 28.2 W, stainless steel coloured

- √ Shelf system
- ✓ Material: aluminium
- √ angular

Shelf system. Aluminium housing. Lighting above and below, 2 mounting variants.

- 12 V, IP20
- stepless control of the light colour from 2700 K warm white to 6500 K cold white
- memory function: the last setting is saved
- dimming function: brightness continuously dimmable
- max. 85 lumen/watt at 6500 K cold white
- the 15 and 30-watt converter can be integrated in the wall shelf
- 200 mm supply cable with mini-plug-in system
- rear panel height 129 mm
- depth 185 mm
- cable outlet rear left
- bearing capacity\* approx. 1 kg/100 mm
- incl. angle adjustment
- LIC LED system compatible

This product contains a light source with the energy efficiency class  $\ensuremath{\mathsf{G}}.$ 

More information about the LIC LED system \*The bearing capacity depends on the wall structure, suitable mounting material for the respective wall type needs to be used.



more infos...



## Technical data

Article type	Shelf system	II
Width	600 mm	١
Material	aluminium	١
Energy efficiency class	G	L
Transformer / converter required	Yes, must be ordered separately	C
Protection class	IP20	(
Cable outlet	cable outlet back left	T
Mounting/Fixing	Wall mounting	L
Note	* The load-bearing capacity depends on the wall condition. Suitable mounting material for the respective wall type is to be used (not included in scope of delivery). the 15 and 30-watt converter can be integrated in the wall shelf	
Shape	angular	II
Memory function	Yes	
Length of the supply line (primary)	200 mm	
Carrying capacity	approx. 1.0 kg/100 mm	

Illuminant included	Yes
Number of storage elements	1
Number of fixing points	2
Lighting	Yes
Colour temperature	2700 K warm white to 6500 K cold white
Colour temperature adjustable	stepless
Type of dimming	brightness continuously dimmable
LIC system compatible	Yes
Plug-in system	with mini plug-in system
Illuminant type	LED
Light yield	max. 85 lumen/watt at 6500 K cold white
Dimming function (composite)	brightness continuously dimmable
Illuminant power	13.8 watts

## Accessories

|--|