



AstraLED SE aluminium coloured

Product number: 7063345

Configuration: set-2, 3900 K neutral white

Configuration options

- 7063314 | individual lamp without switch, 3000 K warm white
- 7063315 | single lamp w. LED Touch s. d., 3000 K warm white
- 7063316 | set-2, 3000 K warm white
- 7063317 | set-3, 3000 K warm white
- 7063319 | set-5, 3000 K warm white
- 7063343 | individual lamp without switch, 3900 K neutral white
- 7063344 | single lamp w. LED Touch s. d., 3900 K neutral white
- 7063345 | set-2, 3900 K neutral white
- 7063346 | set-3, 3900 K neutral white
- 7063347 | set-5, 3900 K neutral white

✓ Under-cabinet/niche light

✓ 3900 K neutral white

✓ 5 watts

Lamp for mounting from below. Aluminium housing, 5 mm, illumination without visible LED points with integrated touch switch.

Individual lamp without or with LED Touch switch and dimmer (w. LED Touch s. d.)

— 5 watt, 24 V, two colour ranges: 3000 K warm white, 3900 K neutral white

— 65 lumen/watt

— brightness continuously dimmable using LED touch switch and dimmer

— 200 mm supply line, 2000 mm connecting line with mini-plug-in system

— additional memory function: the last setting is saved

Set 2, 3, 5 with LED Touch switch and dimmer consisting of:

— 1, 2 or 4 individual lamps with switch (7063314/7063343)

— 1 individual lamp with LED Touch switch and dimmer (7063315/7063344)

— 1 LED converter 2430 (7062250)

— may be extended to 6 lamps

This product contains a light source with the energy efficiency class F.



[more infos...](#)

Technical data

| | | | |
|---|--|---|--|
| Article type | Luminaire | Dimmer | Yes |
| Width | 190 mm | Housing colour | aluminium coloured |
| Energy efficiency class | F | Colour temperature | 3900 K neutral white |
| Transformer / converter required | Yes, included | Type of dimming | brightness continuously dimmable |
| Protection class | III | Plug-in system | with mini plug-in system |
| Mounting/Fixing | Base unit installation (wall unit/ shelf) | Illuminant type | LED |
| Material housing | aluminium | Replaceable illuminant | No |
| Length of connection cable (secondary) | 2.000 mm | Light yield | 65 lumen/watt |
| Switch | Yes | Homogeneous light field without visible LED points | Yes |
| Shape | angular | Touch function | Yes |
| Memory function | Yes | Design | Under-cabinet/niche light |
| Length of the supply line (primary) | 150 mm | Dimming function (composite) | Yes, brightness continuously dimmable |
| Illuminant included | Yes | Illuminant power | 5 watts |

Accessories

| | |
|---------|---|
| 7062252 | LED connection line 24, Connection line/element, white, L 2000 mm |
| 7062250 | LED converter 2430, white |