




AstraLED SE aluminium coloured

Product number: 7063314

Configuration: individual lamp without switch, 3000 K warm white

Configuration options

7063314 | individual lamp without switch, 3000 K warm white
 7063315 | single lamp w. LED Touch s. d., 3000 K warm white
 7063316 | set-2, 3000 K warm white
 7063317 | set-3, 3000 K warm white
 7063319 | set-5, 3000 K warm white
 7063343 | individual lamp without switch, 3900 K neutral white
 7063344 | single lamp w. LED Touch s. d., 3900 K neutral white
 7063345 | set-2, 3900 K neutral white
 7063346 | set-3, 3900 K neutral white
 7063347 | set-5, 3900 K neutral white

✓ Under-cabinet/niche light

✓ 3000 K warm white

✓ 5 watts

Lamp for mounting from below. Aluminium housing, 5 mm, illumination without visible LED points with integrated touch switch.

Individual lamp without or with LED Touch switch and dimmer (w. LED Touch s. d.)

— 5 watt, 24 V, two colour ranges: 3000 K warm white, 3900 K neutral white

— 65 lumen/watt

— brightness continuously dimmable using LED touch switch and dimmer

— 200 mm supply line, 2000 mm connecting line with mini-plug-in system

— additional memory function: the last setting is saved

Set 2, 3, 5 with LED Touch switch and dimmer consisting of:

— 1, 2 or 4 individual lamps with switch (7063314/7063343)

— 1 individual lamp with LED Touch switch and dimmer (7063315/7063344)

— 1 LED converter 2430 (7062250)

— may be extended to 6 lamps

This product contains a light source with the energy efficiency class F.



[more infos...](#)

Technical data

Article type	Luminaire	Dimmer	Yes
Width	190 mm	Housing colour	aluminium coloured
Energy efficiency class	F	Colour temperature	3000 K warm white
Transformer / converter required	Yes, must be ordered separately	Type of dimming	brightness continuously dimmable
Protection class	III	Plug-in system	with mini plug-in system
Mounting/Fixing	Base unit installation (wall unit/ shelf)	Illuminant type	LED
Material housing	aluminium	Replaceable illuminant	No
Length of connection cable (secondary)	2.000 mm	Light yield	65 lumen/watt
Switch	No	Homogeneous light field without visible LED points	Yes
Shape	angular	Touch function	Yes
Memory function	Yes	Design	Under-cabinet/niche light
Length of the supply line (primary)	150 mm	Dimming function (composite)	Yes, brightness continuously dimmable
Illuminant included	Yes	Illuminant power	5 watts

Accessories

7062252	LED connection line 24, Connection line/element, white, L 2000 mm
7062250	LED converter 2430, white