



flow Star GTS 125 F wall conduct

Product number: 4033043
Configuration: white, stainless steel

Configuration options
4033043 | white, stainless steel

✓ Wall sleeve
✓ installation in the wall

With connection to COMPAIR® flow rectangular 125 tube and round **external stainless-steel cover.**
— required opening pressure 100 Pa
— stainless steel cover Ø 197 mm
— tube connector 174 x 82 mm, connector depth 80 mm
— installation depth 314–550 mm, can be shortened to 285 mm, wall penetration Ø about 132 mm
— for the installation of the mounting pipe, a core drilling hole (Ø 132 mm) is recommended

EDELSTAHL® Rost frei

more infos...

Technical data

Article type	Wall sleeve
Material	stainless steel
Properties	can be shortened
Mounting/Fixing	installation in the wall
Certification	stainless
Shortenability	can be shortened to 250 mm
Shape	round
Outer diameter	125 mm

Support depth	80 mm
Installation depth	314–550 mm
Wall box version	with connection to COMPAIR® flow rectangular 125 tube and round external stainless-steel cover
Pipe socket dimension	pipe connector 174 x 82 mm
System dimension	125
Output drive	angular round
Ventilation system	COMPAIR flow 125
Opening pressure	100 Pa