



Q5 5 liters storage water heater

Product number: 6012007

Configuration: black matt/grey, for connection in DE, AT, LU

Configuration options

6012007 | black matt/grey, for connection in DE, AT, LU

- ✓ Hot water tank
- ✓ 5 bar

Storage water heater. The small Q5 5 litre storage heater immediately draws attention with its compact design. Its height is only 145 mm. The special thing about the Q5 is that it can be installed **in or under** practically all kitchen cabinets in a variety of ways. The unit can be mounted horizontally or vertically. Your fitter installs the water heater invisibly behind the skirting board and positions it horizontally or vertically on the side or rear wall.

Advantages of the Q5 5-litre storage water heater over connection to a central hot-water supply system:

- no waiting time
- saves water
- saves energy
- saves money
- no low-pressure faucet necessary

The Q5 also has other advantages over a conventional small under-sink storage water heater:

- **as a pressure-resistant storage heater in high-grade stainless steel, normal high-pressure faucets can be connected**
- **NO annoying dripping from the faucet!**
- thermostat adjustable from the outside
- can be mounted invisibly behind the skirting board
- different installation options
- overall concept, including pressure-resistant safety group and connection set

Warranty

We grant 5 years manufacturer's warranty on the internal stainless steel tank of the storage heater. The other parts are covered by 2 years manufacturer's warranty. For conditions see www.naber.com/en/garantie/.

Technical data:

- connection and temperature controller on the side
- 5 litres filling capacity
- power 2200 watt
- setting range 30-80 °C
- heating up time to 65 °C 18 min
- standby loss 21 Watt
- 145 x 540 x 215 mm (H x W x D)

Installation height of the wall outlet (on-site) 400 mm from the top edge of the floor.



[more infos...](#)

Technical data

Article type	Hot water tank	Warm-up time up to 65 °C	18 min
Height	145 mm	Temperature setting	30–80 °C
Width	540 mm	Max. water pressure	5 bar
Material	stainless steel	Connection to central heating system	Yes
Power	2200 watts	Suitable for	for connection in DE, AT, LU
Note	<p>connection and temperature controller on the side</p> <p>Installation height of the wall outlet (on-site) 400 mm from the top edge of the floor</p> <p>no low-pressure faucet necessary</p> <p>At a water pressure of more than 4 bar, a pressure reducer has to be installed on site in front of the safety group</p>	Volume/Content	5 l
Further	<p>NO annoying dripping from the faucet!</p> <p>thermostat adjustable from the outside</p> <p>can be mounted invisibly behind the skirting board</p> <p>overall concept, including pressure-resistant safety group and connection set</p> <p>different installation options</p>	standby loss	21 Watt