


Twist double plug socket

Product number: 7053075

Configuration: with earthen plug sockets, black matt

Configuration options

- 7053021 | with earthen plug sockets, stainless steel coloured
- 7053025 | with Belgian/French sockets, stainless steel coloured
- 7053059 | with Swiss sockets, stainless steel coloured
- 7053075 | with earthen plug sockets, black matt
- 7053076 | with earthen plug sockets, white matt
- 7053085 | with Belgian/French sockets, black matt
- 7053086 | with Belgian/French sockets, white matt
- 7053189 | with Swiss sockets, black matt

- ✓ Built-in socket element
- ✓ 2 x earthen plug socket
- ✓ round

Socket element. 2-fold.

- 3680 watt/16 A, 250 VAC, IP20
- H05VV-F 3G1
- 3-pin with earthing contact
- 2000 mm mains connection line, earthing contact plug enclosed loosely
- drill Ø 105 mm, for board thicknesses from 8 mm
- increased contact protection
- cable outlet below side



[more infos...](#)

Technical data

Article type	Socket element	Mains plug loosely enclosed	Yes
Drilling diameter	105 mm	Colour bezel	black matt
Mains voltage	250 VAC	Colour socket	black
Protection class	IP20	Installation diameter	115 mm
Cable outlet	cable outlet rear side	Cover/blind type	Turning lid
Max. connected load	3680 watt	Integrated water drain	Yes
Mounting/Fixing	installation on the worktop	Type of socket element	Built-in socket element
Further	3-pole with earthing contact	Wiring	3-wire with free ends bared
Certification	CE	Number of sockets (total)	2
Shape	round	Opening mechanism	Push-to-open
Length of the supply line (primary)	2.000 mm	Touch protection ("child safety lock")	with increased contact protection
Installation depth	40 mm	Worktop thickness	8 mm
Version sockets	2 x earthed plug socket		

Accessories

7053024	Hole saw, Ø 105 mm, for Twist and Duplex
---------	--

Recommendations

7053024	Hole saw, Ø 105 mm, for Twist and Duplex
---------	--