



## Under-sink device TR 1500

Product number: 6011041

Configuration: white

### Configuration options

6011041 | white

- ✓ Hot water tank
- ✓ pressure-free (Open)
- ✓ low pressure

Water heater.

- small water heater 5 litres, white. Open (pressure-free)
- container material in plastic
- high-quality compact insulation
- continuous temperature setting of 35–85 °C
- with frost protection setting "\*" and energy-saving setting "e"
- temperature setting can be limited to stage "I" or stage "e"
- power indicator lamp
- mixed water volume 40 °C 9.5 l
- the outlet of a faucet should always be free
- if possible, do not use a shower fitting
- lowest standby power consumption (about 0,2 kWh at 65 °C/24 h)
- with fastening material, mounting bracket
- switchable safety temperature limiter
- contact/moisture protection IP24D
- power supply 220–240 V
- ready to plug in, connected load 2.2 kW
- weight with water 7.5 kg
- device dimensions (H x W x D) 390 x 258 x 245 mm



[more infos...](#)

### Technical data

Article type	Hot water tank
Operating pressure	low pressure
Width	258 mm
Material	plastic
Energy efficiency class	A
Mains voltage	220–240 V
Protection class	IP24D
Integrated display	power indicator lamp
Note	the outlet of a faucet should always be free if possible, do not use a shower fitting ready to plug in, connected load 2.2 kW
Operating mode	Cable

Certification	CE VDE
Temperature setting	continuous temperature setting of 35–85 °C
Print type	pressure-free (Open)
Weight with water filling	16,53465 lb
Under-sink unit version	high-quality compact insulation With frost protection setting With energy saving position Resettable safety temperature limiter
Standby energy consumption	about 0,2 kWh at 65 °C/24 h
Mixed water quantity	40 °C 9.5 l
Volume/Content	5 l
With mains plug	Yes

### Accessories

6011045	Flow meter, Measuring equipment, red
---------	--------------------------------------