




Under-sink device TR 1500

Product number: 6011041
Configuration: white

Configuration options
6011041 | white

✓ Hot water tank
✓ pressure-free (open)
✓ low pressure

Water heater.
— small water heater 5 litres, white. Open (pressure-free)
— container material in plastic
— high-quality compact insulation
— continuous temperature setting of 35–85 °C
— with frost protection setting "*" and energy-saving setting "e"
— temperature setting can be limited to stage "l" or stage "e"
— power indicator lamp
— mixed water volume 40 °C 9.5 l
— the outlet of a faucet should always be free
— if possible, do not use a shower fitting
— lowest standby power consumption (about 0,2 kWh at 65 °C/24 h)
— with fastening material, mounting bracket
— switchable safety temperature limiter
— contact/moisture protection IP24D
— power supply 220–240 V
— ready to plug in, connected load 2.2 kW
— weight with water 7.5 kg
— device dimensions (H x W x D) 390 x 258 x 245 mm

more infos...

Technical data

Article type	Hot water tank
Height	390 mm
Operating pressure	low pressure
Width	258 mm
Material	plastic
Energy efficiency class	A
Mains voltage	220–240 V
Protection class	IP24D
Integrated display	power indicator lamp
Note	the outlet of a faucet should always be free if possible, do not use a shower fitting ready to plug in, connected load 2.2 kW
Operating mode	Cable

Certification	CE VDE
Temperature setting	continuous temperature setting of 35–85 °C temperature setting can be limited to stage "l" or stage "e"
Print type	pressure-free (open)
Weight with water filling	16,53465 lb
Under-sink unit version	high-quality compact insulation With frost protection setting "*" With energy saving position "e" switchable safety temperature limiter
Standby energy consumption	about 0,2 kWh at 65 °C/24 h
Mixed water quantity	40 °C 9.5 l
Volume/Content	5 l
Material container	plastic
With mains plug	Yes