



## PRIME flow GREENflow OMEGA filter

Product number: 4043080

Configuration: black

### Configuration options

4043080 | black

#### ✓ Exhaust air accessorie

Synthetic activated carbon filter in OMEGA design.

- foam filter with activated carbon (3400 +/- 500 g/m<sup>2</sup> absorber layer)
- hydrophobic (water-repellent)
- regenerable
- easy maintenance/replacement
- special OMEGA design increases the filter area by more than 60 % compared to standard filters
- minimises the pressure losses and the noise of the extractor system

#### Note:

Depending on the cooking behaviour (intensity and frequency) we recommend to change/regenerate the GREENflow OMEGA filter within a period of 3–6 months. When using multiple filters, the time period multiplies by the number of filters.

[more infos...](#)

### Technical data

Article type	Exhaust air accessorie	Temperature application range	–40 °C to +100 °C
Brand	PRIME flow	Pressure loss at 3m/s	15 Pa/m
Width	520 mm	Filter	foam filter with activated carbon (3400 +/- 500 g/m <sup>2</sup> absorber layer)
Properties	hydrophobic (water-repellent) regenerable	Ventilation system	COMPAIR PRIME flow®
Note	Depending on the cooking behaviour (intensity and frequency) we recommend to change/regenerate the GREENflow OMEGA filter within a period of 3–6 months. When using multiple filters, the time period multiplies by the number of filters. easy maintenance/replacement special OMEGA design increases the filter area by more than 60 % compared to standard filters minimises the pressure losses and the noise of the extractor system		