





Evoline® BackFlip USB C

Product number: 8031270

Configuration: with Belgian/French sockets, flush-mount H 2,6 mm,

painted black

Configuration options

8031186 | with earthed plug sockets, stainless steel

8031187 | with earthed plug sockets, painted black

8031188 | with earthed plug sockets, flush-mount H 5 mm, glass black

8031270 | with Belgian/French sockets, flush-mount H 2,6 mm, painted black

8031271 | with Belgian/French sockets, flush-mount H 2,6 mm, stainless steel

8031272 | with Belgian/French sockets, flush-mount H 5 mm, glass black

8031273 | with Swiss sockets, flush-mount H 2,6 mm, stainless steel

8031274 | with Swiss sockets, flush-mount H 2,6 mm, painted black

8031275 | with Swiss sockets, flush-mount H 5 mm, glass black

8031279 | with earthed plug sockets, flush-mount H 5 mm, glass black matt

- √ Built-in socket element
- √ 2 x with Belgian/French socket
- √ angular

Socket element. 2-fold. Rotating with USB C charger (base station).

- installation depth 53 mm
- cut-out dimensions ca. 215 x 88 mm
- 1 x USB charger type C, 5 VDC, IA/I out: 2100 mA
- 2500 mm mains connection line, earthing contact plug enclosed loosely
- flush-mountable
- cable outlet back left







more infos...

Technical data

| Article type | Socket element |
|-------------------------------------|--------------------------------|
| Width | 225,2 mm |
| Cable outlet | cable outlet back left |
| Properties | rotatable |
| Mounting/Fixing | installation on the worktop |
| Material fascia | plastic |
| Certification | CE TÜV |
| Cut-out dimension | approx. 215 x 88 mm |
| Shape | angular |
| Length of the supply line (primary) | 2.500 mm |
| Installation depth | 53 mm |
| Version sockets | 2 x with Belgian/French socket |

| Flush mountable | Yes, H 2.6 mm |
|-----------------------------|--|
| Mains plug loosely enclosed | Yes |
| Colour bezel | painted black |
| Colour socket | black |
| Cover/blind type | Electric |
| Number of USB ports | 1 |
| USB type | USB-C |
| Type of socket element | Built-in socket element |
| Number of sockets (total) | 2 |
| Opening mechanism | Push-to-open |
| USB version | 1 x USB charger type C, 5 VDC, IA/I out: 2100 mA |
| | |